


Sockets, Drive Tools, Accessories



SET NO. J4739C - 1/4" DRIVE 6 PC. TORX® BIT SET

- Not for use on impact applications.
- Weight: 0.38 lbs.


| Product ID No. | Contents |  |
|----------------|--------------|---|
| J4739C | J4739-10W | T10 |
| | J4739-15W | T15 |
| | J4739-20W | T20 |
| | J4739-25W | T25 |
| | J4739-27W | T27 |
| | J4739-30W | T30 |
| | J2584 | Socket Bar 6-1/4" |
| J2590 | Socket Clips | |



1/4" DRIVE STANDARD LENGTH SOCKETS - 6 POINT

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.



| Product ID No. |  in. | B | C | D | E | L | Weight lbs. | ASME Spec. |
|----------------|---|--------|--------|--------|--------|------|-------------|-------------|
| J4704 | 1/8" | 1/4" | 5/32" | 15/32" | 11/32" | 7/8" | 0.02 lbs. | ASME B107.1 |
| J4705 | 5/32" | 17/64" | 31/64" | 11/64" | 11/32" | 7/8" | 0.03 lbs. | ASME B107.1 |
| J4706 | 3/16" | 5/16" | 31/64" | 13/64" | 11/32" | 7/8" | 0.03 lbs. | ASME B107.1 |
| J4707 | 7/32" | 11/32" | 31/64" | 13/64" | 11/32" | 7/8" | 0.02 lbs. | ASME B107.1 |
| J4708 | 1/4" | 11/32" | 31/64" | 7/32" | 11/32" | 7/8" | 0.02 lbs. | ASME B107.1 |
| J4709 | 9/32" | 27/64" | 31/64" | 1/4" | 11/32" | 7/8" | 0.02 lbs. | ASME B107.1 |
| J4710 | 5/16" | 31/64" | 31/64" | 19/64" | 9/16" | 7/8" | 0.03 lbs. | ASME B107.1 |
| J4711 | 11/32" | 33/64" | 33/64" | 11/32" | 17/32" | 7/8" | 0.03 lbs. | ASME B107.1 |
| J4712 | 3/8" | 9/16" | 9/16" | 11/32" | 17/32" | 7/8" | 0.03 lbs. | ASME B107.1 |
| J4714 | 7/16" | 5/8" | 5/8" | 23/64" | 17/32" | 7/8" | 0.05 lbs. | ASME B107.1 |
| J4716 | 1/2" | 11/16" | 11/16" | 23/64" | 17/32" | 7/8" | 0.06 lbs. | ASME B107.1 |
| J4718 | 9/16" | 47/64" | 47/64" | 23/64" | 9/16" | 7/8" | 0.07 lbs. | ASME B107.1 |
| J4720A | 5/8" | 5/8" | 3/8" | 7/8" | 9/16" | 7/8" | 0.09 lbs. | ASME B107.1 |

