

## Main Product Single Throw Safety Switch **Duty Rating** Heavy duty **Device Application** Heavy application Disconnect Type Fusible disconnect Factory Installed Neutral Neutral (factory installed) Number of Poles 60 A **Current Rating** Voltage Rating 250 V DC 240 V AC NEMA 1 steel **Enclosure Rating** Motor power hp 3 Hp at 240 V AC 50-60 Hz for 1 phase motors

10 hp at 250 V DC

7.5 Hp at 240 V AC 50-60 Hz for 3 phase motors 10 Hp at 240 V AC 50-60 Hz for 1 phase motors 15 Hp at 240 V AC 50-60 Hz for 3 phase motors

$\sim$				
Com	nle	ımı	eni	tar\

- Compression y		
Short-circuit current	10 KA for H, K, J or R without fuse rejection clips 200 KA for R with fuse rejection clips 200 kA for J	
Fuse type	H or K R or J	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire (3PH + N)	
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium	
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	5.11 in (129.79 mm)	
Width	6.36 in (161.54 mm)	
Height	14.57 in (370.08 mm)	
Net Weight	8.82 lb(US) (4 kg)	
Services	Field installed kit available	
Condition of use	For USA For Mexico	

## Environment

Certifications	UL listed file E2875

## Ordering and shipping details

Category	00008-H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	3606485893464
Returnability	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	7.50 in (19.05 cm)
Package 1 Length	15.62 in (39.687 cm)
Package 1 Weight	8.82 lb(US) (4 kg)