

ETP Raintight Steel EMT Compression Couplings

Raintight Gland Compression Couplings: 6000NSR Series

Application

- To ground and secure EMT raceway to boxes and enclosures in wet locations.

Features

- UL Listed Raintight.
- No disassembly required.
- Concretetight.

Standard Materials

- Body and nut: steel

Standard Finish

- Body and nut: zinc electroplate

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- UL Listed Raintight



Trade Size (Inches)	Dimensions in Millimeters (Inches)		Weight per 100 pcs kgs (lbs)	Catalog Numbers
	Body Length	Maximum Diameter		
1/2	45.7 (1.80)	27.9 (1.10)	5.4 (12)	6050NSR
3/4	49.0 (1.93)	34.5 (1.36)	8.2 (18)	6075NSR
1	54.6 (2.15)	41.4 (1.63)	11.8 (26)	6100NSR
1-1/4	61.7 (2.43)	52.6 (2.07)	19.1 (42)	6125NSR
1-1/2	63.5 (2.50)	59.0 (2.31)	20.9 (46)	6150NSR
2	74.9 (2.95)	71.0 (2.79)	27.2 (60)	6200NSR
2-1/2	104.1 (4.10)	92.2 (3.63)	70.8 (156)	6250NSR
3	121.2 (4.77)	109.0 (4.29)	98.9 (218)	6300NSR
3-1/2	130.8 (5.15)	121.9 (4.80)	117.0 (258)	6350NSR
4	141.0 (5.55)	134.0 (5.27)	130.6 (288)	6400NSR