



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

Range	TeSys
Product name	TeSys F
Product or Component Type	Magnetic latching contactor
Device short name	CR1F
Device Application	Control
Contactor application	Resistive load Motor control
Utilisation category	AC-3 AC-1 AC-4
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	150 A 104 °F (40 °C) <= 440 V AC AC-3 250 A 104 °F (40 °C) <= 440 V AC AC-1 138 A 104 °F (40 °C) <= 440 V AC AC-4
Motor power kW	75 kW 400 V AC 50/60 Hz AC-4)
Control circuit type	AC 50...400 Hz DC standard
[Uc] control circuit voltage	110 V AC 50...400 Hz 110 V DC
Irms rated making capacity	1700 A
Rated breaking capacity	1500 A 220...440 V 1200 A 500 V 450 A 1000 V 1100 A 660/690 V
[Icw] rated short-time withstand current	1200 A 104 °F (40 °C) - 1 s 1200 A 104 °F (40 °C) - 5 s 1200 A 104 °F (40 °C) - 10 s 700 A 104 °F (40 °C) - 30 s 600 A 104 °F (40 °C) - 1 min 450 A 104 °F (40 °C) - 3 min 350 A 104 °F (40 °C) - 10 min
Associated fuse rating	160 A aM <= 440 V 250 A BS88 <= 440 V 250 A gG <= 440 V
Average impedance	0.45 mOhm - Ith 250 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60158-1 1000 V IEC 60947-4 1000 V BS 775 1500 V VDE 0110 group C
Power dissipation per pole	6 W AC-3 18 W AC-1
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 JIS C8201-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product Certifications	CB Scheme UL CSA EAC CE UKCA
Connections - terminals	Lugs-ring terminals 1 0.19 in ² (120 mm ²) Connector 1 0.19 in ² (120 mm ²) Bars 2 25 x 3 mm Power circuit bolted connection
Tightening torque	159.31 lbf.in (18 N.m)
Operating time	35...40 ms latching 50...100 ms unlatching

Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 104 °F (40 °C)

Complementary

Control circuit voltage limits	Latching 0.85...1.1 Uc Unlatching 0.85...1.1 Uc
Average consumption	1260 VA AC 50...400 Hz latching 10 VA AC 50...400 Hz unlatching 1260 VA DC latching 10 VA DC unlatching

Environment

Protective treatment	TC
Ambient Air Temperature for Operation	5...158 °F (-15...70 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Operating altitude	9842.52 ft (3000 m) without derating
Height	6.69 in (170 mm)
Width	6.44 in (163.5 mm)
Depth	6.73 in (171 mm)
Net Weight	7.72 lb(US) (3.5 kg)

Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	I12
GTIN	3389110547894
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.27 in (21.0 cm)
Package 1 Width	7.87 in (20.0 cm)
Package 1 Length	9.65 in (24.5 cm)
Package 1 Weight	9.03 lb(US) (4.097 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------