

# **SAFETY DATA SHEET**

### SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Thin Wheel - Depressed Center

Product Code: Thin Wheels UPC Number: 66252843216

Other means of identification:

Recommended use of the chemical and restrictions on use: Product Use/Restriction: Abrasive Product.

Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Address: 1 New Bond Street

Worcester, MA 01615

Website: www.Nortonabrasives.com

General Phone Number: 508-795-5000

Emergency phone number:

Emergency Phone Number: 508-795-5000

# SECTION 2: HAZARD(S) IDENTIFICATION

# Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Signal Word: Not applicable.

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Hazard Statements: Not applicable. Precautionary Statements: Not applicable.

# Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Eye: Causes eye irritation. Skin: Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Overexposure may cause headaches and dizziness. Signs/Symptoms: Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 1 of 8 None generally recognized.

#### **Fiberglass**

Inhalation: Fiberglass contained in wheels have fiber diameters greater than 10 um, therefore considered

non-respirable.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

	res	

Chemical Name	CAS#	Ingredient Percent	EC Num.
Inorganic fluorides	Not Applicable	5 - 10 by weight	
Sulfates/Sulfides	No Data	5 - 10 by weight	
Resin	9003-35-4	10 - 30 by weight	
Zirconium dioxide	1314-23-4	5 - 10 by weight	215-227-2
Fiberglass	65997-17-3	1 - 5 by weight	266-046-0
Calcium oxide	1305-78-8	1 - 5 by weight	
Aluminum Oxide, Non-fibrous	1344-28-1	30 - 60 by weight	215-691-6
Titanium dioxide	13463-67-7	1 - 5 by weight	236-675-5

### SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the Eye Contact:

eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing.

Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed:

Other First Aid: Not applicable.

<u>Indication of immediate medical attention and special treatment needed:</u>

Note to Physicians: Not applicable.

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 2 of 8

### SECTION 5: FIRE FIGHTING MEASURES

# Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Unsuitable extinguishing media: Not applicable.

### Specific hazards arising from the chemical:

Hazardous Combustion

Not applicable.

Unusual Fire Hazards:

Byproducts:

Not applicable.

#### Special protective equipment and precautions for fire-fighters:

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) Protective Equipment:

and full protective gear.

Fire Fighting Instructions: Not applicable.

**NFPA Ratings**:

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: 0



### SECTION 6: ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper

personal protective equipment as listed in Section 8.

**Environmental precautions:** 

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Spill Cleanup Measures: Not applicable.

Methods and materials for containment and cleaning up:

Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, Methods for containment:

diking or other means. Provide ventilation.

Methods for cleanup: Clean up spills immediately observing precautions in the protective equipment section. Place into a

suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to

remove trace residue.

Reference to other sections:

Other Precautions: Not applicable.

#### SECTION 7: HANDLING and STORAGE

#### Precautions for safe handling:

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and

incompatible substances. Keep container tightly closed when not in use.

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

# **EXPOSURE GUIDELINES:**

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Inorganic fluorides	PEL-TWA 2.5 mg/m3	REL-TWA 2.5 mg/m3	TLV-TWA 2.5 mg/m3		
Zirconium dioxide			TLV-TWA: 10 mg/m3 as zirconium compounds		
Fiberglass	PEL-TWA: 1 f/cc as Continuous filament glass		TLV-TWA: 1 f/cc as Continuous filament glass TLV-TWA: 5 mg/m3 as Continuous filament glass		
Aluminum Oxide, Non-fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Titanium dioxide			TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Aluminum Oxide, Non-fibrous	OEL-TWA: 10 mg/m3	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		
Titanium dioxide	OEL-TWA: 10 mg/m3 Total particulate/dust (T)	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R)		

#### Appropriate engineering controls:

**Engineering Controls:** Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of

the personal protective equipment.

Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and

face protection regulation, or the European standard EN 166.

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing. Skin Protection Description:

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible

under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if

there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 4 of 8



### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Solid article.

Color: Not determined.

Odor: Odorless.

Odor Threshold: Not determined.

Boiling Point: Not determined.

Melting Point: Not determined.

Density: Not determined.

Solubility: Not determined.

Vapor Density: Not determined.

Vapor Pressure: Not determined.

Evaporation Rate: Not determined.

pH: Not determined.

Viscosity: Not determined.

Coefficient of Water/Oil

Distribution:

Not determined.

Flammability: Not determined.

Flash Point: None.

Lower Flammable/Explosive Limit: Not applicable.

Upper Flammable/Explosive Limit: Not applicable.

Auto Ignition Temperature: Not applicable.

Explosive Properties: Excessive dust accumulation could present a potential combustible dust hazard.

VOC Content: Not determined.

### SECTION 10: STABILITY and REACTIVITY

Reactivity:

Reactivity: Not applicable.

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

 Thin Wheel - Depressed Center
 66252843216

 Revison Date: 03/31/2015
 5 of 8

#### <u>Hazardous Decomposition Products:</u>

Special Decomposition Products: Not applicable.

# SECTION 11: TOXICOLOGICAL INFORMATION

#### TOXICOLOGICAL INFORMATION:

Acute Toxicity: This product has not been tested for its toxicity.

Carcinogens:							
	ACGIH	NIOSH	OSHA	IARC	NTP		MEXICO
Aluminum Oxide, Non-fibrous	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	No Data	No Data		A4 Not Classifiable as a Human Carcinogen
Titanium dioxide	No Data	No Data	No Data	No Data	No Data		A4 Not Classifiable as a Human Carcinogen

Resin:

RTECS Number: SM8542500

Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than Skin:

lethal dose value ] (RTECS)

Ingestion: Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS)

**Zirconium dioxide:** 

RTECS Number: ZH8800000

Fiberglass:

RTECS Number: LK3651000

Calcium oxide:

RTECS Number: EW3100000

**Aluminum Oxide, Non-fibrous:** 

RTECS Number: BD1200000

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or Inhalation:

functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema;

Related to Chronic Data - death] (RTECS)

Titanium dioxide:

XR2275000 RTECS Number:

Skin - Human Standard Draize test.: 300 ug/3D-I - [mild] (RTECS) Skin:

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration: 1 mg/kg - [Lungs, Thorax, or Respiration -

Other changes Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of

inflammation ] (RTECS)

Ingestion: Oral - Rodent rat TDLo - Lowest published toxic dose: 60 gm/kg - [Gastrointestinal - Hypermotility,

diarrhea Gastrointestinal - Other changes ] (RTECS)

# SECTION 12: ECOLOGICAL INFORMATION

# **Ecotoxicity:**

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 6 of 8

### SECTION 13: DISPOSAL CONSIDERATIONS

#### Description of waste:

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

### **SECTION 14: TRANSPORT INFORMATION**

UN number: Not regulated as hazardous material for transportation. UN proper shipping name: Not regulated as hazardous material for transportation. Transport hazard class(es): Not regulated as hazardous material for transportation. Packing group: Not regulated as hazardous material for transportation. Environmental hazards: Not regulated as hazardous material for transportation. Special precautions for user: Not regulated as hazardous material for transportation.

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

### **Inventory Status**

	Japan ENCS	EINECS Number	South Korea KECL	Australia AICS	Canada DSL
Resin					Listed
Zirconium dioxide					Listed
Fiberglass					Listed
Aluminum Oxide, Non-fibrous	(1) -23	262-373-8	KE-01012	Listed	Listed
Titanium dioxide	(1)-558		KE-33900	Listed	Listed

	TSCA Inventory Status		
Resin	Listed		
Zirconium dioxide	Listed		
Fiberglass	Listed		
Calcium oxide	Listed		
Aluminum Oxide, Non-fibrous	Listed		
Titanium dioxide	Listed		

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 7 of 8

#### **Aluminum Oxide, Non-fibrous:**

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

**Zirconium dioxide:** 

EC Number: 215-227-2

Fiberglass:

EC Number: 266-046-0

**Aluminum Oxide, Non-fibrous:** 

EC Number: 215-691-6

<u>Titanium dioxide</u>:

EC Number: 236-675-5

# **State Right To Know**

	RI	MN	IL	PA	MA
Zirconium dioxide					Listed
Aluminum Oxide, Non-fibrous	Listed	Listed	No Data	Listed	Listed
Titanium dioxide	Listed	Listed	No Data	Listed	Listed

	NJ		
Aluminum Oxide, Non-fibrous	Listed: NJ Hazardous List; Substance Number: 2891		
Titanium dioxide	No Data		

# SECTION 16: ADDITIONAL INFORMATION

#### **HMIS Ratings:**

HMIS Health Hazard: 1 HMIS Fire Hazard: 1 HMIS Reactivity: 0

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	

SDS Creation Date: August 15, 2009 SDS Revision Date: March 31, 2015 MSDS Revision Notes: GHS Update

 $\label{lem:copyright} \mbox{Copyright} \mbox{@ 1996-2015 Actio Corporation. All Rights Reserved.}$ 

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843216 8 of 8