

Product data sheet

Characteristics

8536SBG2V08H30

NEMA Motor Starter, Type S, nonreversing, Size 0, 18A, 3 pole, 240 VAC coil, Motor Logic SSOLR, open style, +options



Main

| | |
|---------------------------|------------------------|
| Product or component type | Starter |
| Type | S |
| Control Circuit Type | Common control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 208 V AC 60 Hz |
| Motor starter type | Non reversing |
| Current Rating | 18 A |
| Number of Poles | 3P |
| Number of Phases | 3 phase |
| Horsepower Rating | 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC |
| Maximum Voltage Rating | 600 V AC |
| Control Units | No control units |
| Thermal overload type | Solid state Motor Logic class 10/20 |
| Electrical connection | Screw clamp terminals |
| NEMA size | 0 |
| Maximum Height | 10.00 in (254 mm) |
| Maximum Depth | 5.55 in (141 mm) |
| Maximum Width | 5.98 in (152 mm) |



Environment

| | |
|------------------------|----------------------------|
| Enclosure Type | NEMA 1 painted sheet steel |
| Product certifications | CSA NEMA UL Listed |

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 21191 - 8502,36 SA,SB(NOT S*R,T,W) |
| Discount Schedule | CP1 |
| GTIN | 00785901995555 |
| Package weight(Lbs) | 7.4 lb(US) (3.36 kg) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|-----------------------|---|
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| China RoHS Regulation |  China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|