

Industrial Air Circulators - 115V

Oscillating Unit Packs



Oscillating Wall Mount

Adjustable Floor

3 Year Warranty

FEATURES

- 2 Mounting Options
- Guard Meets OSHA Standards
- 115V, 60 Hz, 1/3 HP, 1 Phase, 3 Speed, Totally Enclosed Ball Bearing Motors
- Galvanized Steel Propeller
- 15 Foot Three Conductor Supply Cord and Plug
- All Stocked

All Parts Packaged in One UPS Shippable Carton

OSCILLATING PERFORMANCE 115V

Prop Dia.	CFM			RPM			Motor Number	F.L. Amps
	High	Med.	Low	High	Med.	Low		
24"	5548	4699	4062	1110	958	856	0-3B	3.2
30"	7794	5943	5143	1091	871	759	0-3B	3.2

Performance Ratings are conducted in accordance with AMCA Standard 230-99.



EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Ship Wt.	List Price
71567	I-24-OAP	24"	Adjustable Floor	1/3	86	\$788
71565	I-24-OIW	24"	Wall Mount*	1/3	57	\$716
71568	I-30-OAP	30"	Adjustable Floor	1/3	95	\$827
71566	I-30-OIW	30"	Wall Mount*	1/3	61	\$770

Wall Mount is supplied with the required Safety Cable Kit. *Used with EDP# 37772 Mounting Bracket. Unit Pack - Motor, Specified Style Mounting, Propeller & Guard shipped in a single carton.

MOTOR TILT ADJUSTMENTS

TYPE	TILT UP OR DOWN (IN DEGREES)	
	OSCILLATING	
	UP	DOWN
FLOOR	20°	20°
WALL	0°	20°

0° = Horizontal Plane

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

Oscillating Assembled Fan Heads †



Industrial Head Assembly

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Ship Wt.	List Price
71610	24-IAC-MGBO	24"	Head Assembly	1/3	46	\$644
38422	30-IAC-MGBO	30"	Head Assembly	1/3	56	\$687

†Motor, Guard, and Propeller Pre-Assembled

Note: Oscillating fan heads are NOT to be used in upside down position.

30" Head Assembly is UPS OverSize 2.