


# Sockets, Drive Tools, Accessories



## 1/4" DRIVE STANDARD LENGTH SOCKETS - 8 POINT

- Proto® 8 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.




Product ID No.	 in.	B	C	D	E	L	Weight lbs.	ASME Spec.
<b>J4708S</b>	1/4"	31/64"	31/64"	1/4"	17/32"	7/8"	0.03 lbs.	ASME B107.1
<b>J4710S</b>	5/16"	9/16"	9/16"	1/4"	17/32"	7/8"	0.05 lbs.	ASME B107.1
<b>J4712S</b>	3/8"	11/16"	11/16"	1/4"	17/32"	7/8"	0.06 lbs.	ASME B107.1

## 1/4" DRIVE STANDARD LENGTH SOCKETS - 12 POINT

- Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.



Product ID No.	 in.	B	C	D	E	L	Weight lbs.	ASME Spec.	AS Spec.
<b>J4705T</b>	5/32"	3/8"	3/8"	13/64"	5/16"	7/8"	0.02 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4706T</b>	3/16"	5/16"	7/16"	13/64"	5/16"	7/8"	0.02 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4707T</b>	7/32"	11/32"	7/16"	13/64"	5/16"	7/8"	0.02 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4708T</b>	1/4"	3/8"	7/16"	7/32"	5/16"	7/8"	0.02 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4709T</b>	9/32"	27/64"	27/64"	17/64"	9/16"	7/8"	0.02 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4710T</b>	5/16"	15/32"	15/32"	19/64"	9/16"	7/8"	0.02 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4711T</b>	11/32"	1/2"	1/2"	11/32"	9/16"	7/8"	0.03 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4712T</b>	3/8"	35/64"	35/64"	23/64"	17/32"	7/8"	0.04 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4714T</b>	7/16"	5/8"	5/8"	3/8"	17/32"	7/8"	0.05 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4716T</b>	1/2"	11/16"	11/16"	23/64"	17/32"	7/8"	0.05 lbs.	ASME B107.1	AS954E S3.8.1
<b>J4718T</b>	9/16"	47/64"	47/64"	23/64"	17/32"	7/8"	0.07 lbs.	ASME B107.1	AS954E S3.8.1

