

Temperature Accessories

Contact Probes

80PK-1 and 80PJ-1 Bead Probe

- 80PK-1 : Type-K thermocouple for general purpose applications • 80PJ-1 operates
- with J-type thermometers
- Measurement range: -40 to 260°C

80BK Low-cost Integrated DMM Probe

- Type-K thermocouple with standard banana iack
- Convenient one piece construction
- Compatible with DMMs with temperature measurement functions
- Measurement range : -40 to 260°C

80PK-2A Immersion Probe

- Type-K thermocouple for use in liquids and gels
- Measurement range: -40 to 982°C

80PK-3A Surface Probe

- Type-K thermocouple for flat or curved surfaces such as plates and rollers
- Measurement range: 0 to 260°C

80PK-4A Air Probe

- Type-K thermocouple for use in air or gases, except halides and sulfides
- Bead protected by perforated baffle
- Measurement range: -40 to 816°C

80PK-5A and 80PT-5A Piercing Probe

- 80PK-5A : Type-K thermocouple suitable for food industry, liquids and gels except halides and sulfides
- 80PT-5A operates with T-type thermometers • Measurement range: -40 to 260°C



- **80PK-6A Exposed Probe**
- Type-K thermocouple provides fast response for non-reducing air and gases, except halides, sulfides, and vacuums
- Measurement range: -40 to 816°C

80PK-7 Industrial Surface Probe

- Type-K thermocouple for surfaces in rugged environment
- Durable ribbon sensor
- Measurement range: -127 to 600°C

80PK-8 Pipe Clamp Temperature Probe

- Type-K thermocouple for fast temperature and superheat measurements of pipe surfaces • Durable ribbon sensor
- Measurement range: -29 to 149°C for pipe diameters from 6.4 to 34.9mm



80PK-9 and 80PJ-9 General Purpose Probe

- 80PK-9 : Type-K thermocouple surface, air and non-caustic
- gases • 80PJ-9 operates with J-type
- thermometers • Measurement range :
 - -40°C to 260°C

80T-150U Universal Temperature Probe

- Compatible with Fluke DMM
- High accuracy, fast reading for low voltage (below 24Vac, 60V dc) applications
- Measurement range: -50 to 150°C
- or 1mV/°F (switchable)



• Output: 1mV/°C

80TK Thermocouple Module

- Converts a DMM to a
- thermometer • For use with type-K thermocouples in low voltage applications (below 24Vac,



- 60V dc) • Measurement
 - range: -50 to 1000°C (probe dependent)





Temperature Accessories

Non-Contact Probes

80T-IR & 80PK-IR Infrared Temperature Probes

- Ideal for applications where object being measured cannot be touched
- Provides instant and highly repeatable readings
- 80T-IR (for DMMs) and 80PK-IR (for digital thermometers) have automatic shut-off after 10 minutes
- Senses infrared energy emitted by an object
 Measurement range: -18 to 260°C





Other Temperature Accessories

80CK-M & 80CJ-M type K & J Male

- Mini-Connectors • Isothermal screw terminal for K or J wire
- Suitable for up to 20 guage thermocouple wire
- Color coded to industry standards (K-yellow, J-black)
- Two per package

80AK

- Adapts Type-K thermocouple mini-connector to dual banana plug inputs
- Measurement range and accuracy: probe dependent
- Suitable for low voltage applications (below 30V AC, 60V DC)

80PK-EXT, 80PJ-EXT and 80PT-EXT Extension Wire Kits

- Extending and repairing J, K ot T-type thermocouple wires
- Kit includes 3 meters of thermocouple wire and 1 pair of male/female mini-connectors
- Maximum continuous exposure temperature : 260°C
- 80PK-EXT is compatible with K-type thermometers, 80PJ-EXT is designed for Jtype thermometers and PT-EXT for T-type thermometers



Thermocouple Plug Kits 700TC1

A kit of 10 mini-plug connectors Type J (black), one Type K (yellow), one Type T (blue), one Type E (purple), one Type B or CU (white), one Type L (J-DIN) (blue), one Type U (T-DIN) (brown), one Type C (red), one Type N (orange), one



700TC2

A kit of 7 mini-plug connectors Type J (black), two Type K (yellow), two Type T (blue), one Type R/S (green), one



744 787

••

••

1

| thermometers | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------|--------|----------|----|------------|---------------|--------------|--------|------------------|---------------|---------------|---------------|---------------|--------|------------|----|--------|-----|--------|----|---------------|------------------------|--------|-----|-----|-----|-----|-----|-----|----------|----------------|----------|-----------|------------|------|------|-----|
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Temperature Probe Compatibility Chart | | | | | | | | | | | | Ì | | | | Ì | | ĺ | | | | | | | ĺ | | ĺ | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | ľ | | | | | | \square | ľ | 1 | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | 1 I | | | | | | . | |
| | | | | | | | | | | | | | | | | | | | | | | ۱, | | 38 | | | | | | 1 I | | | | | | . | |
| | | 12B | | | | | | | | | | | | | | | | | | | | | series | 33/ | | | | | | 1 I | | | | | | . | |
| | 0 | 1 | | | | | | 日 | Ξ [; | 8060A / 8062A | | | | | | | | | | | | 9 | se | က် | | | | | | 1 I | | | | | | . | |
| | 7-600 | 12 / | | | H | | | Series | 26/79 Series III | 8 | | Ħ | Ξİ | | | | | | | | | 5 | t ; | 2 | | | | | | 1 I | | | | | | . | |
| | 4 | / 1 | | | Series III | 73 Series III | 21/75 Series | E | EI. | ~ | S. | 85 Series III | 87 Series III | Series | 189 Series | | ~ | | Series | | | 100/000 11/27/23/27 | 5 1 | /32 | | | | | | 1 I | | | | | | . | |
| | 0 | Ξ | | | jų. | i ii | S | S | S. | A | Ξ. | Ë, | Ξ. | er | Į. | | 41B | | ١ğ | | | 5 | 3 | 33 | | | | | | 1 I | | | | | | . | |
| | 7-300 | \sim | | | | N N | E I | 23/77 | Ë ? | 6 | 83 Series | Š | Ϋ́ | 20 | 6 | 2 | \sim | 0 | ől | | 45 EOG/EOD | | 0. | | ß | | ~ | - | | 0 | | ~ | 4 | 2 | 741B | 743B | 4 |
| Contact Droken | 1 | 10 | 16 | 27 | 2 | 73 | 21 | 133 | 28 | 8 | 8 | 85 | 28 | 187 | <u>8</u> | 86 | 33 | 123 | 190 | 43 | 142 | 8 5 | | 30/ | 705 | 712 | 713 | 714 | 715 | 716 | TIT | 718 | 724 | 725 | 2 | 4 | 744 |
| Contact Probes 80PK-1 through 80PK-9 | | | 2 | 1 | <u>,</u> | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 1 | | 1 | 1 | 1 | 1 | | | - | | _ | | • | _ | | \vdash | <u> </u> | • | • | • | • | - |
| 80T-150U | | • | 4 | 1 | | 1 | | | • | | | | | | | | - | | • | | 1 | - | - | - | | - | | | • | | \vdash | <u> </u> | i | | | • | |
| 80PJ-1, 80PJ-9 | | • | | • | - | • | - | - | - | - | - | - | - | • | - | • | - | • | - | - | - | | | - | | - | | • | - | $ \neg $ | $ \rightarrow$ | - | | ŏ | | ŏ | |
| 80PT-5A | | | | | - | | | - | - | | - | | - | | - | | - | | - | - | + | | | - | | - | | ě | - | -+ | | - | | ě | | ě | |
| 80BK | | | • | | | | - | + | - | | - | | - | • | • | | - | | - | - | | + | - | | | | | - | - | -+ | | - | +- | <u> </u> | - | - | - |
| Non-Contact Probes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | 1 | 1 | | | |
| 80T-IR | | ٠ | • | ۲ | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | | | | • | | | | ٠ | | | | | | | | |
| 80PK-IR | | | 2 | | | | | | | | | | | 2 | 2 | | | | | | | | | | | | | • | | | | | • | • | • | • | ۲ |
| Miscellaneous | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 80AK | | | ۰ | | | | | | | | | | | • | | | | | | | | | | | | | | | | | | | | | | | |
| SOTK | | • | • | ٠ | ٠ | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | | | | • | | | | ۲ | | | | • | • | • | • | • |
| 80CK-M | | | <u> </u> | | | | | -+ | \rightarrow | _ | _ | _ | _ | | _ | | | | _ | | | | | _ | | _ | | • | | | \vdash | — | ↓● | ↓ ● | | | |
| SOCJ-M | | | <u> </u> | - | <u> </u> | | _ | + | + | + | \rightarrow | | _ | | _ | | _ | | _ | -+ | | | | _ | | _ | | • | | | \vdash | | ╇ | 1. | | - | - |
| 80PK-EXT, 80PJ-EXT 80PT-EXT | | | | | | | | _ | — | _ | _ | | _ | | _ | | _ | | _ | | - | | | _ | | _ | | • | | | \vdash | — | • | | • | • | |
| OUP1-EA1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | • | | | | | | • | | • | • |

Pub_ID: 10015-eng Rev. 02 1: Requires 80TK 2: Requires 80AK

cy: