

Product availability: Stock - Normally stocked in distribution facility



### Main

Product	Surge protection device
Range	SurgeLogic
Device Short Name	EMA

### Complementary

Surge Current	160 kA
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
Connection	Lugs AWG 10...AWG 2 copper 35.40 lbf.in (4 N.m)
MCOV	150 V
Nominal Discharge Current	20 kA
SCCR	200 kA
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault
Provided Equipment	Alarm enable/disable switch Surge counter Dry contacts
Device Mounting	Surface
Height	11.42 in (290 mm)
Width	11.02 in (280 mm)
Depth	5.31 in (135 mm)

### Environment

Enclosure Rating	NEMA 1
Enclosure Material	Grey painted sheet steel
Standards	CSA C22.2 No 8 UL 1449:ed. 4 UL 1283:ed. 5
Ambient Operating	149 °F (65 °C)

### Ordering and shipping details

Category	08464 - SURGE PROTECTION EMA
Discount Schedule	DE1B
GTIN	00785901565932
Package weight(Lbs)	6.39 kg (14.08 lb(US))
Returnability	Yes
Country of origin	MX

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>