



## Main

|                                 |                                  |
|---------------------------------|----------------------------------|
| Range of Product                | Harmony 9001SK                   |
| Product or Component Type       | Head for illuminated push-button |
| Device short name               | 9001SK                           |
| Type of operator                | Spring return                    |
| Operator profile                | Red flush, unmarked              |
| Operator additional information | Plastic guard                    |
| Light block supply              | Direct 120 V AC/DC               |

## Complementary

|   |  |
|---|--|
| Bezel material                              | Plastic  |
| Mounting diameter                           | 1.18 in (30 mm)  |
| Shape of signaling unit head                | Octagonal  |
| Light source                                | Red LED  |
| Bulb base                                   | BA 9s  |
| [Us] rated supply voltage                   | 120 V AC/DC  |
| Contacts type and composition               | Without contact block  |
| Connections - terminals                     | Screw clamp terminals 1 x 0.22...2 x 1.5 mm <sup>2</sup> EN/IEC 60947-1  |
| Tightening torque                           | 7.08 lbf.in (0.8 N.m) EN/IEC 60947-1   |
| Shape of screw head                         | Cross slotted  |
| Mechanical durability                       | 5000000 cycles   |
| Operating position                          | Any position   |
| [Ie] rated operational current              | 0.55 A 125 V, DC-13, A600-Q600 NEMA  |
| [Ui] rated insulation voltage               | 250 V 3)EN/IEC 60947-1   |
| [Uimp] rated impulse withstand voltage      | 2.5 kV EN/IEC 60947-1  |
| Positive opening                            | Without  |
| Short-circuit protection                    | 10 A cartridge fuse EN/IEC 60947-5-1   |
| [Ith] conventional free air thermal current | 10 A   |
| [Icm] rated short-circuit making capacity   | 12 KA 600 V AC-15, 7200 VA<br>15 KA 480 V AC-15, 7200 VA<br>30 KA 240 V AC-15, 7200 VA<br>60 KA 120 V AC-15, 7200 VA<br>0.27 KA 250 V DC-13<br>0.55 KA 125 V DC-13<br>0.1 kA 600 V DC-13 |
| Rated breaking capacity                     | 1.2 KA 600 V AC-15, 720 VA<br>1.5 KA 480 V AC-15, 720 VA<br>3 KA 240 V AC-15, 720 VA<br>6 KA 120 V AC-15, 720 VA<br>0.27 KA 250 V DC-13<br>0.55 KA 125 V DC-13<br>0.1 kA 600 V DC-13     |
| Net Weight                                  | 0.40 lb(US) (0.181 kg)   |
| Device presentation                         | Basic element  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>UL 508<br>EN/IEC 60947-5-1<br>JIS C 4520<br>JIS C 852<br>CSA C22.2 No 14 |
| Product Certifications                | UL 508<br>NEMA   |
| Protective treatment                  | TC   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)   |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6  |
| Shock resistance                      | 50 gn IEC 60068-2-27   |
| Electrical shock protection class     | Class II IEC 61140   |
| IP degree of protection               | IP66 IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                               |

## Ordering and shipping details

|                       |                     |
|-----------------------|---------------------|
| Category              | 21429-9001 SK,SKY   |
| Discount Schedule     | CS1                 |
| GTIN                  | 3389118038486       |
| Nbr. of units in pkg. | 1                   |
| Package weight(Lbs)   | 6.40 oz (181.437 g) |
| Returnability         | No                  |
| Country of origin     | MX                  |

## Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 1.80 in (4.572 cm) |
| Package 1 width        | 2.10 in (5.334 cm) |
| Package 1 Length       | 3.60 in (9.144 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[9001SK1L38LRR](#)