## Product data sheet Characteristics

# 9080GCB150

Circuit protector, Linergy, thermal magnetic overcurrent, track mount, 15.0A, 125 VAC / 65 VDC

Product availability: Stock - Normally stocked in distribution facility

SQUARE D

Price\*: 72.00 USD



#### Main

		and the second s
Range of product	9080GCB	
Product or component type	Circuit Protector	Jo
Trip Unit Type	Thermal-magnetic	elle Dispersional dispersion of the property o
Electrical Connection	Box lugs	5

#### Complementary

Protection type	Overcurrent	
Contact operation	Trip-free E	
Device application	Industrial Application	
Line Rated Current	15 A	<u>v</u>
Number of Poles	1P	<del>t</del>
Votlage Rating	65 V DC 125 V AC	<u> </u>
Wire Size	AWG 16AWG 10 copper	्रे -
Wire stripping length	0.5 in (12.70 mm)	.i.
Terminal Tightening Torque	Control circuit 7 lbf.in (0.79 N.m) cage type connector	v n
Terminal Rating	Factory wiring only	ـــــــــــــــــــــــــــــــــــــ
Operating Temperature	-22140 °F (-3060 °C)	
Calibration Temperature	70 °F (21 °C)	
Mounting support	9080GH track 35 mm DIN rail	- included in the control of the con
Height	3.45 in (87.63 mm)	
Maximum Width	3.15 in (80.01 mm)	<u></u> 
Maximum Depth	0.5 in (12.70 mm)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

#### Environment

Product certifications	CE CSA file 025490 class 3211 07 UL recognized E233026 CCN QVNU2	
Standards	CSA C22.2 No 235 UL 1077 DIN 57470	

#### Ordering and shipping details

Crucining and companie actuals		
Category	21703 - 9080 GCB	
Discount Schedule	CP5	
GTIN	00785901481003	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.16 lb(US) (0.07 kg)	
Returnability	Yes	
Country of origin	DE	

### Packing Units

Package 1 Height	3.40 in (8.636 cm)	
Package 1 width	3.70 in (9.398 cm)	
Package 1 Length	1.00 in (2.540 cm)	

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	

#### Contractual warranty

Warranty	18 months	