

9001KS11FB

selector switch Ø 30 - 2 position - stay put - long handle - black



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------|--------------------------|
| Commercial Status | Commercialised |
| Range of product | Harmony 9001KS |
| Product or component type | Complete selector switch |
| Device short name | 9001K |
| Type of operator | Stay put |
| Operator profile | Black long handle |

Complementary

| | |
|-------------------------------|----------------------------------|
| Bezel material | Chromium plated metal |
| Mounting diameter | 1.18 in (30 mm) |
| Product weight | 0.38 lb(US) (0.172 kg) |
| Shape of signaling unit head | Octagonal |
| Operator position information | 2 positions 90° |
| Contacts type and composition | Without contact block |
| Mechanical durability | 500000 cycles |
| Product compatibility | 9001KA2, mounting on side 1 or 2 |

Environment

| | |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Protective treatment | TC |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Class of protection against electric shock | Class II |
| IP degree of protection | IP66 conforming to IEC 60529 |
| NEMA degree of protection | NEMA 4 NEMA 3R NEMA 3 NEMA 2 NEMA 13 NEMA 12 NEMA 1 |
| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14 |
| Product certifications | NEMA UL 508 |
| Vibration resistance | 7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn conforming to IEC 60068-2-27 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-----------------------|---------------------------------------------------|
| Category | 21426 - 9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 00785901322900 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.27 |
| Product availability | Stock - Normally stocked in distribution facility |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|--------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 0921 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|