Product data sheet Characteristics

9001KS53FB

selector switch \emptyset 30 - 3 position spring returnlong handle - black



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main	
Commercial Status	Commercialised
Range of product	Harmony 9001KS
Product or component type	Complete selector switch
Device short name	9001K
Type of operator	Spring return (to centre)
Operator profile	Black long handle

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Product weight	0.38 lb(US) (0.172 kg)	
Shape of signaling unit head	Octagonal	
Operator position information	3 positions +/- 45°	
Contacts type and composition	Without contact block	
Mechanical durability	500000 cycles	
Product compatibility	9001KA1, mounting on side 1 or 2	

Environment

Environment		
Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Class of protection against electric shock	Class II	
IP degree of protection	IP66 conforming to IEC 60529	
NEMA degree of protection	NEMA 4 NEMA 3R NEMA 3 NEMA 2 NEMA 13 NEMA 12 NEMA 12	
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14	
Product certifications	NEMA UL 508	
Vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	50 gn conforming to IEC 60068-2-27	

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	00785901048497	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.28	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0921 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
i chou	To monute

