

# Product data sheet

## Characteristics

# 9001W31

## white Fresnel lens cap - for pilot light Ø 30



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



### Main

|                                       |                                 |
|---------------------------------------|---------------------------------|
| Commercial Status                     | Commercialised                  |
| Range of product                      | Harmony 9001K<br>Harmony 9001SK |
| Accessory / separate part designation | Fresnel lens cap                |
| Accessory / separate part type        | Lens cap                        |
| Accessory / separate part category    | Spare parts                     |
| Accessory / separate part destination | Pilot light                     |

### Complementary

|                             |                        |
|-----------------------------|------------------------|
| Mounting diameter           | 1.18 in (30 mm)        |
| Cap/Operator or lens colour | White                  |
| Product weight              | 0.01 lb(US) (0.005 kg) |

### Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 21433 - 9001 ACCESS FOR K,KX,SK                   |
| Discount Schedule     | CS1   |
| GTIN                  | 00785901056089                                    |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 0.01  |
| Product availability  | Stock - Normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | MX  |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS                     | Compliant - since 0921 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                    | Reference not containing SVHC above the threshold                                     |

### Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.