

9007LA4

9007C limit switch lever - zinc - 90° fork -
outside steel rollers



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|-----------------------------|---|
| Commercial Status | Commercialised |
| Range of product | 9007 |
| Series name | Heavy duty |
| Product or component type | Limit switch lever |
| Device short name | 9007C |
| Associated head | 9007C |
| Associated complete product | 9007C |
| Movement of operating head | Rotary |
| Type of operator | Cast zinc stay put 90° forked arm with rollers length: 1.5 in - offset: - - |
| Type of roller | 2 steel outside roller diameter: 0.75 in - width: 0.25 in |
| Type of approach | Lateral approach |
| Positive opening | Without |

Complementary

| | |
|------------------|-----------------|
| Switch actuation | By specific cam |
| Product weight | 0.1 lb(US) |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -20...185 °F |
| Ambient air temperature for storage | -20...185 °F |
| Environmental characteristic | Standard environment |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 21493 - 9007 ARMS FOR AW,C |
| Discount Schedule | DS1 |
| GTIN | 00785901867135 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.10 |
| Product availability | Stock - Normally stocked in distribution facility |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Not Green Premium product |
| RoHS | Will be Compliant on 3Q2014 |
| Product environmental profile | Available Download Product Environmental |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|
