

HDL36060

Molded Case Circuit Breaker



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	Commercialised
Product or component type	Molded Case Circuit Breaker
Range of product	PowerPact H
[In] rated current	60 A
Poles description	3P
Breaking capacity	20 kA 250 V DC 14 kA 600 V AC 18 kA 480 V AC 25 kA 240 V AC
[Ue] rated operational voltage	250 V DC 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Trip unit technology	Thermal-magnetic
Product certifications	CSA IEC UL listed
Mounting mode	Unit mount
Breaking capacity code	D
Electrical connection	Lugs line Lugs load
AWG gauge	14...3/0 AWG aluminium/copper
Magnetic hold current	800 A
Magnetic tripping current	1450 A

Ordering and shipping details

Category	01110 - HD,JD UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901577959
Nbr. of units in pkg.	1
Package weight(Lbs)	4.07
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0832 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.