

HOM215GFI

MINIATURE CIRCUIT BREAKER 120/240V 15A

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|--------------------------------|---|
| Commercial Status | Commercialised |
| Product or component type | Miniature Circuit Breaker |
| Range of product | Homeline |
| [In] rated current | 15 A |
| Product certifications | CSA UL listed |
| [Ue] rated operational voltage | 120/240 V AC |
| Mounting mode | Plug-in |
| Poles description | 2P |
| Short-circuit current | 10 kA |
| Number of spaces required | 2 |
| Circuit breaker type | Ground fault protecting class A 6 mA |
| Circuit breaker application | HACR rated |
| Electrical connection | Screw clamp terminals |
| AWG gauge | 14...6 AWG copper 12...4 AWG aluminium |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 00147 - HOM 2 POLE GFI CB,40A MAX |
| Discount Schedule | DE3D |
| GTIN | 00785901303190 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.15 |
| Product availability | Stock - Normally stocked in distribution facility |
| Returnability | Y |
| Country of origin | MX |

Contractual warranty

| | |
|--------|----------|
| Period | Lifetime |
|--------|----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.