

HOM24L70RB

LOAD CENTER HOM MLO 240V 70A 1PH 2SP

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	Homeline
Load center type	Fixed Mains (lugs)
[In] rated current	70 A
Number of spaces	2
Short-circuit current	10 kA
Number of circuits	4
Number of tandem circuit breakers	2
Network number of phases	1 phase
[Ue] rated operational voltage	120/240 V AC

Complementary

AWG gauge	14...4 AWG copper 12...3 AWG aluminium
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded galvanized steel
Cover finish	Gray baked enamel
Product certifications	UL listed file E-6294

Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R
Discount Schedule	DE3C
GTIN	00785901061175
Nbr. of units in pkg.	1
Package weight(Lbs)	5.03
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

Contractual warranty

Period	Lifetime
--------	----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.