Product data sheet Characteristics

HOM612L100RB LOAD CENTER HOM MLO 240V 100A 1PH 6SP

Product availability: Stock - Normally stocked in distribution facility

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	Homeline
Load center type	Fixed Mains (lugs)
[In] rated current	100 A
Number of spaces	6
Short-circuit current	10 kA
Number of circuits	12
Number of tandem circuit breakers	6
Network number of phases	1 phase
[Ue] rated operational voltage	120/240 V AC

Complementary

AWG gauge	81 AWG copper 81 AWG aluminium
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded galvannealed steel
Cover finish	Gray baked enamel
Product certifications	UL listed file E-6294

Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R	
Discount Schedule	DE3C	
GTIN	00785901061205	
Nbr. of units in pkg.	1	
Package weight(Lbs)	9.92	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	MX	

Contractual warranty

	•
Period	Lifetime