

# LC2D18G7

TeSys D reversing contactor - 3P(3 NO) - AC-3  
- <= 440 V 18 A - 120 V AC coil





## Main

|   |  |
|---|--|
| Commercial Status                           | Commercialised   |
| Range of product                            | TeSys D  |
| Product or component type                   | Reversing contactor  |
| Device short name                           | LC2D   |
| Contactors application                      | Motor control<br>Resistive load  |
| Utilisation category                        | AC-1<br>AC-3   |
| Device presentation                         | Preassembled with reversing power busbar   |
| Poles description                           | 3P   |
| Pole contact composition                    | 3 NO   |
| [Ue] rated operational voltage              | <= 300 V DC for power circuit<br><= 690 V AC 25...400 Hz for power circuit   |
| [Ie] rated operational current              | 32 A (<= 140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit<br>18 A (<= 140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit   |
| Motor power kW                              | 10 kW at 660...690 V AC 50/60 Hz<br>10 kW at 500 V AC 50/60 Hz<br>9 kW at 415...440 V AC 50/60 Hz<br>7.5 kW at 380...400 V AC 50/60 Hz<br>4 kW at 220...230 V AC 50/60 Hz  |
| Motor power hp                              | 15 hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>10 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>5 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>5 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>3 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>1 hp at 115 V AC 50/60 Hz for 1 phase motors |
| Control circuit type                        | AC 50/60 Hz  |
| Control circuit voltage                     | 120 V AC 50/60 Hz  |
| Auxiliary contact composition               | 1 NO + 1 NC  |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947   |
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 32 A at <= 140 °F (60 °C) for power circuit<br>10 A at <= 140 °F (60 °C) for signalling circuit  |
| Irms rated making capacity                  | 300 A at 440 V for power circuit conforming to IEC 60947<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>140 A AC for signalling circuit conforming to IEC 60947-5-1   |
| Rated breaking capacity                     | 300 A at 440 V for power circuit conforming to IEC 60947   |
| [Icw] rated short-time withstand current    | 240 A <= 104 °F (40 °C) 1 s power circuit<br>145 A <= 104 °F (40 °C) 10 s power circuit<br>84 A <= 104 °F (40 °C) 1 min power circuit<br>40 A <= 104 °F (40 °C) 10 min power circuit<br>140 A 100 ms signalling circuit<br>120 A 500 ms signalling circuit<br>100 A 1 s signalling circuit                             |
| Associated fuse rating                      | 35 A gG at <= 690 V coordination type 2 for power circuit<br>50 A gG at <= 690 V coordination type 1 for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947-5-1   |
| Average impedance                           | 2.5 mOhm at 50 Hz - Ith 32 A for power circuit   |

|                               |   |
|-------------------------------|---|
| [Ui] rated insulation voltage | 600 V for signalling circuit certifications UL<br>600 V for signalling circuit certifications CSA<br>690 V for signalling circuit conforming to IEC 60947-1<br>600 V for power circuit certifications UL<br>600 V for power circuit certifications CSA<br>690 V for power circuit conforming to IEC 60947-4-1   |
| Electrical durability         | 1 Mcycles 32 A AC-1 at Ue ≤ 440 V<br>1.65 Mcycles 18 A AC-3 at Ue ≤ 440 V   |
| Power dissipation per pole    | 2.5 W AC-1<br>0.8 W AC-3  |
| Protective cover              | With  |
| Interlocking type             | Mechanical  |
| Mounting support              | Plate<br>Rail   |
| Standards                     | EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14   |
| Product certifications        | BV<br>CCC<br>CSA<br>DNV<br>GL<br>GOST<br>RINA<br>UL<br>LROS   |
| Connections - terminals       | Power circuit: screw clamp terminals 2 cable(s)<br>0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Power circuit: screw clamp terminals 1 cable(s)<br>0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Power circuit: screw clamp terminals 2 cable(s)<br>0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Power circuit: screw clamp terminals 1 cable(s)<br>0...0.01 in <sup>2</sup> (1...6 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Power circuit: screw clamp terminals 2 cable(s)<br>0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Power circuit: screw clamp terminals 1 cable(s)<br>0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Control circuit: screw clamp terminals 2 cable(s)<br>0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 1 cable(s)<br>0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 2 cable(s)<br>0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 1 cable(s)<br>0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 2 cable(s)<br>0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end<br>Control circuit: screw clamp terminals 1 cable(s)<br>0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end |
| Tightening torque             | Control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver flat Ø 6 mm  |
| Operating time                | 4...19 ms opening<br>12...22 ms closing   |

|                          |   |
|--------------------------|---|
| Safety reliability level | B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1<br>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 |
| Mechanical durability    | 15 Mcycles  |
| Operating rate           | 3600 cyc/h at ≤ 140 °F (60 °C)  |

## Complementary

|                                 |   |
|---------------------------------|---|
| Coil technology                 | Without built-in suppressor module  |
| Control circuit voltage limits  | 0.85...1.1 Uc at 140 °F (60 °C) operational 60 Hz<br>0.8...1.1 Uc at 140 °F (60 °C) operational 50 Hz<br>0.3...0.6 Uc at 140 °F (60 °C) drop-out 50/60 Hz |
| Inrush power in VA              | 70 VA at 68 °F (20 °C) (cos φ 0.75) 50 Hz<br>70 VA at 68 °F (20 °C) (cos φ 0.75) 60 Hz  |
| Hold-in power consumption in VA | 7 VA at 68 °F (20 °C) (cos φ 0.3) 50 Hz<br>7.5 VA at 68 °F (20 °C) (cos φ 0.3) 60 Hz  |
| Heat dissipation                | 2...3 W at 50/60 Hz   |
| Auxiliary contacts type         | Type mirror contact (1 NC) conforming to IEC 60947-4-1<br>Type mechanically linked (1 NO + 1 NC) conforming to IEC 60947-5-1                              |
| Signalling circuit frequency    | 25...400 Hz   |
| Minimum switching current       | 5 mA for signalling circuit   |
| Minimum switching voltage       | 17 V for signalling circuit   |
| Non-overlap time                | 1.5 ms on energisation (between NC and NO contact)<br>1.5 ms on de-energisation (between NC and NO contact)   |
| Insulation resistance           | > 10 MOhm for signalling circuit  |

## Environment

|   |  |
|---|--|
| IP degree of protection                               | IP2x front face conforming to IEC 60529  |
| Protective treatment                                  | TH conforming to IEC 60068-2-30  |
| Pollution degree                                      | 3  |
| Ambient air temperature for operation                 | 23...140 °F (-5...60 °C)   |
| Ambient air temperature for storage                   | -76...176 °F (-60...80 °C)   |
| Permissible ambient air temperature around the device | -40...158 °F (-40...70 °C) at Uc   |
| Operating altitude                                    | 9842.52 ft (3000 m) without derating in temperature  |
| Fire resistance                                       | 1562 °F (850 °C) conforming to IEC 60695-2-1   |
| Flame retardance                                      | V1 conforming to UL 94   |
| Mechanical robustness                                 | Shocks contactor closed 15 Gn for 11 ms<br>Shocks contactor open 10 Gn for 11 ms<br>Vibrations contactor closed 4 Gn, 5...300 Hz<br>Vibrations contactor open 2 Gn, 5...300 Hz |
| Height  | 3.03 in (77 mm)  |
| Width   | 3.54 in (90 mm)  |
| Depth   | 3.39 in (86 mm)  |
| Product weight  | 1.56 lb(US) (0.707 kg)   |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 22346 - CTR,D-LINE,OPEN,REVERSING-NEW             |
| Discount Schedule     | I12   |
| GTIN                  | 00785901207467                                    |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 1.79  |
| Product availability  | Stock - Normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | ID  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0627 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|