



PLENUM-RATED UNIT HEATER PHFP25 SERIES

CONCEALED SPACE USE - ZERO CLEARANCE



NEUTRAL GRAY

IDEAL SPACES | Between Finished Ceiling and Drop Ceiling; Plenum Space; Freeze Protection

COLORS | Neutral Gray

DIMENSIONS | 14" L x 12-1/2" H x 14" D **TEMP RANGE** | 40°-90° F **CFM** | 150

- Plenum-rated approved for installations in concealed spaces (between finished ceiling and drop ceiling, plenum space, or inside a plenum). It may be installed in areas that are not readily accessible and may be installed for freeze protection
- 18-gauge all steel casing with polyester powder coat finish for corrosion protection
- Steel finned low-watt density element. High limit thermal cutout automatically shuts off current in event of overheating and reactivates the heater when temperature returns to normal
- Fan delay control. feature allows only warm air to be distributed; optional alarm (240V) to alert automatic thermal limit tripped (Model AFL240)
- Built-in thermostat
- Control box gasket to keep out moisture and dust; NEMA 12 construction
- Fan motor completely enclosed, permanently lubricated and thermally protected
- Single point field wiring connection for easy installation and maintenance

MODELS & SPECIFICATIONS

CATALOG NO.	UPC NUMBER	VOLTS	HZ	KW	PHASE	BTU/HR	FPM	RISE	SHIP AMPS	SHIP WT. (LBS)
PHFP25	6 85360 14954 7	240	50/60	2.5	1	8530	1880	60°F	10.7	26
		208	50/60	1.9		6398		46°F	9.42	

ACCESSORIES

CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)
AFL240	6 8536015347 6	Thermal Limit Alarm	1

