

POLY-TEMP[®] MD MEDIUM DENSITY THREAD SEAL TAPE

WWW.ANTISEIZE.COM

Product Description

POLY-TEMP[®] MD Medium Density Thread Seal Tape is a general purpose PTFE Thread Seal Tape designed to be used on all types of metal and plastic pipe threads.

Our **POLY-TEMP**[®] Tapes are made from 99.9% virgin PTFE resins for optimum purity and performance. **POLY-TEMP**[®] **MD** Medium Density Thread Seal Tape is malleable to easily conform to thread profiles to ensure a positive seal.

Because **POLY-TEMP**[®] **MD** Medium Density Thread Seal Tape is composed of pure PTFE, it touts an extremely broad range of chemical compatibilities and is unaffected by most chemicals and concentrations.

POLY-TEMP[®] MD Medium Density Thread Seal Tape is our most popular grade of thread sealing tape and has been Industry Leader for over 30 years.

Features & Benefits

- Meets FDA and USDA requirements
- UL Listed
- Ideal for all tapper thread connections
- PTFE's high lubricity makes for easy assembly
- Only 3 wraps need for most applications
- Chemically inert, non-Toxic
- Suitable for oxygen service
- Our most popular grade of Thread Seal Tape
- Easy to handle and apply
- Temperature range from -400F to 550F (-240C to 287C)
- Pressures up to 10,000psi (Liquid), 2000 psi (Gas)
- Connections can be put into service right away, no dry time
- Never dries out and an unlimited shelf life.
- Meets MIL-T-27730A
- Extremely versatile.

Typical Properties

Property	Value	
Color	White	
Thickness	3.5 mils	
Specific Gravity	0.7 to 0.8g/cc	
Toxicity	Non toxic	
RoHS2	Compliant	

Cautions

Read all information on labels and Material Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use.

Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

Available In:

Size:	½" x 60 "	¹ ⁄ ₄ "x520"	¹ / ₂ "x260"	′ ½" x520 "	½" x1296 "
P/N:	16006	16025	16030	16035	16040
Size:	³∕₄" x260 "	¾"x520	<u>" 1"x26</u>	<u>0"1"x520</u>)"
P/N:	16045	16050	16055	16060	
Size:	Counter	Display	½" x260 "	1/2"x520"	' ¾"x520"
P/N:				16035A	
P/N:			16030A	16035A	16050A

 $\textbf{POLY-TEMP}^{\texttt{B}}$ IS A REGISTERED TRADEMARK OF ANTI-SEIZE TECHNOLOGY