


The Apex heritage of qual

For more than half a century Apex has maintained a position of leadership in industrial fastening tools. Today, Apex stands ready to improve the productivity of assembly operations around the world with unsurpassed tool performance and customer service.

Precision Fit

Apex quality begins with select raw materials. Only carefully chosen, high grade tool steel is used. Each tool is manufactured to the tightest tolerances in the industry...most are even tighter than licensing agreement requirements. Our bits meet the most stringent government and military specifications where applicable (i.e. MIL-B-9946/5 for HTS Hi-Torque® bits used in aerospace assembly).



Precision fit of Apex tools eliminates "cam-out" and premature bit failure.

Apex sockets, nutsetters and universal wrenches have hex tolerances that are on average 48% tighter than DIN and 35% tighter than ANSI requirements. With Apex you are assured of an exact, sure fit.

All Apex sockets and extensions have the tightest tolerances for straightness and concentricity in the



Precision-manufactured Apex tools are virtually wobble-free.

industry. Tools that run true perform better and last longer.

Lasting Performance

Each Apex tool is tempered with our proprietary heat treating process that lets you select the degree of hardness your particular application requires. Choose from tough, non-brittle durability that stands up to torque, to the hardest heat treat available in the industry for the ultimate in wear resistance.



Apex offers a choice of three heat treat hardness levels in many of our screwdriver bits to match the application. These heat treats are specified by a letter suffix as follows:

- X - Hardest heat treat in the industry**
- I - Intermediate hardness**
- R - Lowest hardness**

Our experienced staff can help in selecting the best heat treat for your particular application.



Torx® Bits



1/4" Hex Power Drive

| Part Number | Driver Size | | Body Diameter | | Overall Length | |
|-------------|-------------|------|---------------|-----|----------------|-----|
| | | | In. | mm | In. | mm |
| 49-TX-05 | T-5 | .055 | .119 | 3.0 | 1 15/16 | 49 |
| 49-A-TX-05 | T-5 | .055 | .119 | 3.0 | 2 3/4 | 70 |
| 49-B-TX-05 | T-5 | .055 | .119 | 3.0 | 3 1/2 | 89 |
| 49-TX-06 | T-6 | .065 | .119 | 3.0 | 1 15/16 | 49 |
| 49-A-TX-06 | T-6 | .065 | .119 | 3.0 | 2 3/4 | 70 |
| 49-TX-07 | T-7 | .077 | .119 | 3.0 | 1 15/16 | 49 |
| 49-A-TX-07 | T-7 | .077 | .119 | 3.0 | 2 3/4 | 70 |
| 49-B-TX-07 | T-7 | .077 | .119 | 3.0 | 3 1/2 | 89 |
| 49-C-TX-07 | T-7 | .077 | .119 | 3.0 | 6 | 152 |
| 49-TX-08 | T-8 | .090 | .119 | 3.0 | 1 15/16 | 49 |
| 49-A-TX-08 | T-8 | .090 | .119 | 3.0 | 2 3/4 | 70 |
| 49-B-TX-08 | T-8 | .090 | .119 | 3.0 | 3 1/2 | 89 |
| 49-C-TX-08 | T-8 | .090 | .119 | 3.0 | 6 | 152 |
| 49-TX-09 | T-9 | .097 | .119 | 3.0 | 1 15/16 | 49 |
| 49-A-TX-09 | T-9 | .097 | .119 | 3.0 | 2 3/4 | 70 |
| 49-B-TX-09 | T-9 | .097 | .119 | 3.0 | 3 1/2 | 89 |
| 49-C-TX-09 | T-9 | .097 | .119 | 3.0 | 6 | 152 |
| 49-TX-10 | T-10 | .107 | .150 | 3.8 | 1 15/16 | 49 |
| 49-A-TX-10 | T-10 | .107 | .150 | 3.8 | 2 3/4 | 70 |
| SD-4693 | T-10 | .107 | .150 | 3.8 | 3 | 75 |
| 49-B-TX-10 | T-10 | .107 | .150 | 3.8 | 3 1/2 | 89 |
| 49-C-TX-10 | T-10 | .107 | .150 | 3.8 | 6 | 152 |
| 49-TX-15 | T-15 | .128 | .150 | 3.8 | 1 15/16 | 49 |
| 49-A-TX-15 | T-15 | .128 | .150 | 3.8 | 2 3/4 | 70 |
| 49-B-TX-15 | T-15 | .128 | .150 | 3.8 | 3 1/2 | 89 |
| 49-C-TX-15 | T-15 | .128 | .150 | 3.8 | 6 | 152 |
| 49-TX-20 | T-20 | .151 | .171 | 4.3 | 1 15/16 | 49 |
| 49-A-TX-20 | T-20 | .151 | .171 | 4.3 | 2 3/4 | 70 |
| 49-B-TX-20 | T-20 | .151 | .171 | 4.3 | 3 1/2 | 89 |
| 49-TX-20-5 | T-20 | .151 | .171 | 4.3 | 5 | 127 |
| 49-C-TX-20 | T-20 | .151 | .171 | 4.3 | 6 | 152 |
| 49-TX-25 | T-25 | .173 | .193 | 4.9 | 1 15/16 | 49 |
| 49-A-TX-25 | T-25 | .173 | .193 | 4.9 | 2 3/4 | 70 |
| 49-B-TX-25 | T-25 | .173 | .193 | 4.9 | 3 1/2 | 89 |
| 49-C-TX-25 | T-25 | .173 | .193 | 4.9 | 6 | 152 |
| 49-TX-27 | T-27 | .195 | .215 | 5.5 | 1 15/16 | 49 |
| 49-A-TX-27 | T-27 | .195 | .215 | 5.5 | 2 3/4 | 70 |
| 49-B-TX-27 | T-27 | .195 | .215 | 5.5 | 3 1/2 | 89 |
| 49-C-TX-27 | T-27 | .195 | .215 | 5.5 | 6 | 152 |
| 49-TX-30 | T-30 | .216 | .236 | 6.0 | 1 15/16 | 49 |
| 49-A-TX-30 | T-30 | .216 | .236 | 6.0 | 2 3/4 | 70 |
| 49-B-TX-30 | T-30 | .216 | .236 | 6.0 | 3 1/2 | 89 |
| 49-C-TX-30 | T-30 | .216 | .236 | 6.0 | 6 | 152 |
| 49-TX-40 | T-40 | .260 | .309 | 7.8 | 1 15/16 | 49 |
| 49-A-TX-40 | T-40 | .260 | .309 | 7.8 | 2 3/4 | 70 |
| 49-B-TX-40 | T-40 | .260 | .309 | 7.8 | 3 1/2 | 89 |
| 49-C-TX-40 | T-40 | .260 | .309 | 7.8 | 6 | 152 |



1/4" Hex Power Drive – Torxalign®

| Part Number | Driver Size | | Body Diameter | | Overall Length | |
|--------------|-------------|------|---------------|-----|----------------|----|
| | | | In. | mm | In. | mm |
| 49-TX-08-W | T-8 | .090 | .119 | 3.0 | 1 15/16 | 49 |
| 49-TX-10-W | T-10 | .107 | .150 | 3.8 | 1 15/16 | 49 |
| 49-TX-15-W | T-15 | .128 | .150 | 3.8 | 1 15/16 | 49 |
| 49-A-TX-15-W | T-15 | .128 | .150 | 3.8 | 2 3/4 | 70 |
| 49-B-TX-15-W | T-15 | .128 | .150 | 3.8 | 3 1/2 | 89 |
| 49-TX-20-W | T-20 | .151 | .171 | 4.3 | 1 15/16 | 49 |
| 49-B-TX-20-W | T-20 | .151 | .171 | 4.3 | 3 1/2 | 89 |
| 49-TX-25-W | T-25 | .173 | .193 | 4.9 | 1 15/16 | 49 |
| 49-TX-27-W | T-27 | .195 | .215 | 5.5 | 1 15/16 | 49 |
| 49-TX-30-W | T-30 | .216 | .236 | 6.0 | 1 15/16 | 49 |
| 49-B-TX-30-W | T-30 | .216 | .236 | 6.0 | 3 1/2 | 89 |



1/4" Hex Power Drive – Tamper Resistant**

| Part Number | Driver Size | | Body Diameter | | Overall Length | |
|--------------|-------------|------|---------------|-----|----------------|-----|
| | | | In. | mm | In. | mm |
| 49-TX-10-H | T-10-H | .107 | .150 | 3.8 | 1 15/16 | 49 |
| 49-A-TX-10-H | T-10-H | .107 | .150 | 3.8 | 2 3/4 | 70 |
| 49-TX-15-H | T-15-H | .128 | .150 | 3.8 | 1 15/16 | 49 |
| 49-A-TX-15-H | T-15-H | .128 | .150 | 3.8 | 2 3/4 | 70 |
| 49-B-TX-15-H | T-15-H | .128 | .150 | 3.8 | 3 1/2 | 89 |
| 49-A-TX-20-H | T-20-H | .151 | .171 | 4.3 | 2 3/4 | 70 |
| 49-B-TX-20-H | T-20-H | .151 | .171 | 4.3 | 3 1/2 | 89 |
| 49-C-TX-20-H | T-20-H | .151 | .171 | 4.3 | 6 | 152 |

**Tamper resistant Torx® bits are available on a restricted distribution basis. Contact your local Apex representative for details.



1/4" Hex Power Drive with Finder Sleeves

| Part Number | Driver Size | Sleeve Number* | | Sleeve Diameter | | Overall Length | |
|-------------|-------------|----------------|------|-----------------|------|----------------|----|
| | | | | In. | mm | In. | mm |
| M-32-TX-15 | T-15 | M | .128 | .437 | 12.1 | 3 1/2 | 89 |
| M-32-TX-20 | T-20 | M | .151 | .437 | 12.1 | 3 1/2 | 89 |
| NP-32-TX-25 | T-25 | NP | .173 | .437 | 12.1 | 3 3/4 | 95 |
| R-32-TX-27 | T-27 | R | .195 | .563 | 14.3 | 3 5/8 | 92 |
| S-32-TX-30 | T-30 | S | .216 | .625 | 15.9 | 3 7/8 | 98 |

*See page 14 for Sleeve Selection



7/16" Hex Power Drive

| Part Number | Driver Size | | Body Diameter | | Overall Length | |
|-------------|-------------|------|---------------|------|----------------|----|
| | | | In. | mm | In. | mm |
| 48-TX-40 | T-40 | .260 | .277 | 7.0 | 3 1/2 | 89 |
| 48-TX-45 | T-45 | .306 | .323 | 8.2 | 3 1/2 | 89 |
| 48-TX-50 | T-50 | .346 | .363 | 9.2 | 3 1/2 | 89 |
| 48-TX-55 | T-55 | .440 | .503 | 12.8 | 3 3/4 | 95 |