

ARMSTRONG® Tool Steel Long Pin Punch

- Made in the USA - Quality and Availability
- Manufactured From Shock Resistant Tool Steel for Unequalled Strength, Toughness, and Durability; Higher Hardness Without Brittleness
- Full Shank Heat Treat is A 2 Step Process Where the Entire Length of the Tool is Hardened and Tempered, Then the Struck End is Drawn Back for to Resist "Mushrooming" and "Chipping" Extending the Life of the Tool"
- Pin Area Precision Ground to Prevent Any "Binding" in Work Area
- Modified Parabolic Head Directs the Striking Force to the Center of the Tool for Greater Resistance to "Mushrooming" and "Chipping"
- Black Oxide Finish and Visible "Wear Safety Goggles" Reminder
- Hex Stock Fits More Securely in A Punch & Chisel Holder and Also Reduces the Tendency to Roll on Work Surfaces
- Meets or Exceeds ASME B107.48M and Us Federal Spec. GGG-P-831F



Cat. No.	UPC No.	Packaging	Point Diameter	Stock Size	Overall Length	Product Weight	Shelf Pack Qty.
70-041	781412700411	Bagged	1/8 in	5/16 in	8.000 in	0.12 lb	1
70-042	781412700428	Bagged	5/32 in	5/16 in	8.000 in	0.12 lb	1
70-043	781412700435	Bagged	3/16 in	3/8 in	8.000 in	0.18 lb	1
70-044	781412700442	Bagged	7/32 in	3/8 in	8.000 in	0.18 lb	1
70-045	781412700459	Bagged	1/4 in	3/8 in	8.000 in	0.19 lb	1
70-047	781412700473	Bagged	5/16 in	7/16 in	8.000 in	0.25 lb	1
70-049	781412700497	Bagged	3/8 in	1/2 in	8.000 in	0.37 lb	1

ARMSTRONG® Brass Pin Punch

- Made in the USA - Quality and Availability
- Non Marring - Ideal for Work Where A Strong Positive Blow is Necessary Without Damaging the Work Surface
- Non-Sparking; Ideal for Working on Heavy Equipment, in Mines and Explosive Atmospheres Where Spark Free" is Required"
- Pin Area Precision Ground to Prevent Any "Binding" in Work Area



Cat. No.	UPC No.	Packaging	Point Diameter	Stock Size	Overall Length	Product Weight	Shelf Pack Qty.
70-295	781412702958	Bagged	1/2 in	3/8 in	4.000 in	0.19 lb	1
70-296	781412702965	Bagged	3/8 in	1/2 in	6.000 in	0.32 lb	1