

## ARMSTRONG® Solid Handle, Phillips Tip, Round Shank Screwdrivers

- Made in the USA - Quality and Availability
- Precision Machined, Blasted Tips Provide Superior Fit Between the Tip and the Fastener Reducing Slippage and Fastener Wear
- Full Shaft Heat Treat Provides Superior Strength That Resists Tip Wear and Shank Twisting / Breakage
- Fully Polished Chrome Plated Blade Provides a High Luster That Prevents Corrosion
- Tri-Lobe Handle Conforms to the Hand for Optimal Power and Comfort
- Solid Impact Resistant Acetate Handle for Uncompromising Durability
- Broad, Shallow Flutes with Chamfered Edges Provide a High Efficiency, High Torque Handle with No Sharp Edges
- Larger Than Average Handle Lengths and Diameters for Optimal Power and Comfort
- Domed Handle for Comfortably Applying Added Pressure
- Meets or Exceeds ASME B107.15-2002



| Cat. No. | UPC No.      | Packaging | Screw Size | Tip Thickness | Tip Size | Blade Length | Blade Diameter | Overall Length | Handle Size (Dia. X Length) | Product Weight | Shelf Pack Qty. |
|----------|--------------|-----------|------------|---------------|----------|--------------|----------------|----------------|-----------------------------|----------------|-----------------|
| 66-153   | 781412661538 | Bagged    | P1         | 0.188 in      | #1       | 3.000 in     | 0.188 in       | 6.750 in       | 1.06 in x 3.75 in           | 0.16 lb        | 1               |
| 66-155   | 781412661552 | Bagged    | P1         | 0.188 in      | #1       | 6.000 in     | 0.188 in       | 9.750 in       | 1.06 in x 3.75 in           | 0.18 lb        | 1               |
| 66-156   | 781412661569 | Bagged    | P2         | 0.250 in      | #2       | 4.000 in     | 0.250 in       | 8.250 in       | 1.18 in x 4.25 in           | 0.23 lb        | 1               |
| 66-158   | 781412661583 | Bagged    | P2         | 0.250 in      | #2       | 8.000 in     | 0.250 in       | 12.250 in      | 1.18 in x 4.25 in           | 0.30 lb        | 1               |
| 66-161   | 781412661613 | Bagged    | P3         | 0.313 in      | #3       | 6.000 in     | 0.313 in       | 11.000 in      | 1.25 in x 5.00 in           | 0.37 lb        | 1               |
| 66-164   | 781412661644 | Bagged    | P4         | 0.375 in      | #4       | 8.000 in     | 0.375 in       | 13.500 in      | 1.25 in x 5.50 in           | 0.56 lb        | 1               |

## ARMSTRONG® Solid Handle, Slotted Tip, Stubby Screwdrivers

- Made in the USA - Quality and Availability
- Precision Machined, Blasted Tips Provide Superior Fit Between the Tip and the Fastener Reducing Slippage and Fastener Wear
- Full Shaft Heat Treat Provides Superior Strength That Resists Tip Wear and Shank Twisting / Breakage
- Fully Polished Chrome Plated Blade Provides a High Luster That Prevents Corrosion
- Tri-Lobe Handle Conforms to the Hand for Optimal Power and Comfort
- Solid Impact Resistant Acetate Handle for Uncompromising Durability
- Broad, Shallow Flutes with Chamfered Edges Provide a High Efficiency, High Torque Handle with No Sharp Edges
- Larger Than Average Handle Lengths and Diameters for Optimal Power and Comfort
- Domed Handle for Comfortably Applying Added Pressure



| Cat. No. | UPC No.      | Packaging | Screw Size | Tip Thickness | Tip Size | Blade Length | Blade Diameter | Overall Length | Handle Size (Dia. X Length) | Product Weight | Shelf Pack Qty. |
|----------|--------------|-----------|------------|---------------|----------|--------------|----------------|----------------|-----------------------------|----------------|-----------------|
| 66-230   | 781412662306 | Bagged    | #5, 6, 7   | 0.030 in      | 3/16 in  | 1.000 in     | 0.188 in       | 3.000 in       | 1.18 in x 2.00 in           | 0.10 lb        | 1               |
| 66-232   | 781412662320 | Bagged    | #8, 9      | 0.037 in      | 1/4 in   | 1.500 in     | 0.250 in       | 3.500 in       | 1.18 in x 2.00 in           | 0.13 lb        | 1               |