

Campbell® Marine Alloy Trawl Chain - Drums

- Made of High Strength, Heat Treated Alloy Steel
- Designed for Use with the Larger Nets in the Trawling Industry
- Special Heat Treatment for the Trawling Industry
- Grade 80 Strengths
- Hallmarking: "NETS8" and Date Code
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Made in the USA
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Cat. No.	UPC No.	Chain Type	Inside Length	Inside Width	Finish	Working Load Limit	Feet Per Package	Weight Per Package
1/2 in	0407512	020418190452	Long Link	3.15 in	0.97 in	Bright	12000 lb	300 ft	570 lb
5/8 in	0407612*	020418190469	Long Link	3.71 in	1.00 in	Bright	18100 lb	150 ft	473 lb
3/4 in	0407712	020418190476	Long Link	3.99 in	1.29 in	Bright	28300 lb	100 ft	480 lb

* These Items are Made to Order

Campbell® Grade 70, Transport Chain - Drums

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Can Be Used in Accordance with Department of Transportation Regulations
- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Zinc Electroplate with Yellow Chromate Conversion Coating
- Hallmarking: "C7" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Drums, Order Unit is "Feet"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Cat. No.	UPC No.	Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0510412	020418063763	0.31 in	0.94 in	0.46 in	3150 lb	800 ft	12.8	752 lb
5/16 in	0510512	020418063800	0.33 in	1.15 in	0.48 in	4700 lb	550 ft	10.4	561 lb
3/8 in	0510612	020418063848	0.40 in	1.36 in	0.57 in	6600 lb	400 ft	8.8	600 lb
7/16 in	0510712	020418063886	0.47 in	1.29 in	0.67 in	8750 lb	300 ft	9.3	636 lb
1/2 in	0510812	020418063916	0.53 in	1.70 in	0.75 in	11300 lb	200 ft	7.1	520 lb