

## Campbell® Grade 70, Transport Chain - Half Drums

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Can Be Used in Accordance with Department of Transportation Regulations
- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Zinc Electroplate with Yellow Chromate Conversion Coating
- Hallmarking: "C7" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Half Drums, Order Unit is "Feet"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Cat. No.	UPC No.	Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0510410	020418063749	0.31 in	0.94 in	0.46 in	3150 lb	400 ft	12.8	376 lb
5/16 in	0510510	020418063787	0.33 in	1.15 in	0.48 in	4700 lb	275 ft	10.4	280 lb
3/8 in	0510610	020418063824	0.40 in	1.36 in	0.57 in	6600 lb	200 ft	8.8	300 lb
1/2 in	0510810	020418063893	0.53 in	1.70 in	0.75 in	11300 lb	100 ft	7.1	260 lb

## Campbell® Grade 70, Transport Chain - Round Pails

- Designed for Use in Load Binding, Towing, Logging and Other Applications Requiring High Strength
- Can Be Used in Accordance with Department of Transportation Regulations
- Standard Material: Heat Treated Carbon Steel
- Standard Finish: Zinc Electroplate with Yellow Chromate Conversion Coating
- Hallmarking: "C7" and "USA"
- Proof Tested
- Design Factor: 4 to 1
- Packaged in Pails, Order Unit is "Each"
- Do Not Use for Overhead Lifting
- DO NOT EXCEED THE WORKING LOAD LIMIT



Trade Size	Cat. No.	UPC No.	Material Diameter	Inside Length	Inside Width	Working Load Limit	Feet Per Package	Links Per Foot	Weight Per Package
1/4 in	0510413	020418063770	0.31 in	0.94 in	0.46 in	3150 lb	150 ft	12.8	139 lb
5/16 in	0510513	020418063817	0.33 in	1.15 in	0.48 in	4700 lb	100 ft	10.4	102 lb
3/8 in	0510613	020418063855	0.40 in	1.36 in	0.57 in	6600 lb	75 ft	8.8	113 lb