

# NEER Anti-Short Bushings and Cable Staples

## AS: Thermoplastic

### Applications


- These anti-short bushings are used in the terminations of flexible metal conduit and armored cables. Insert into inside diameter of each termination point to protect the conductors from the sharp edges of the raceway where cut.

### Standard Material

- Plastic



AS-0



## SN: Cable Staples

### Applications

- To secure nonmetallic sheathed cable and type SE/U cable to wooden mounting structure.

### Standard Material


- Steel

Note:

- SN cable staples are furnished in plastic containers.



SN



Trade Size (Inches)	Catalog Number	Dimensions in Inches/ Millimeters		For Cable Sizes
		A	B	
<b>Bagged (Packed in Printed Polybags)</b>				
5/16	AS-0-100	0.57/ 14.5	0.64/ 16.3	14-2, 14-3, 12-2, Armored Cable; 5/169 Flexible Conduit
3/8	AS-1-100	0.67/ 17.0	0.66/ 16.8	14-4, 12-3, 6-1, 4-1, Armored Cable; 3/89 Flexible Conduit
7/16	AS-2-100	0.61/ 15.5	0.82/ 20.8	12-4, 10-2, 10-3, 2-1, Armored Cable; 7/169 Flexible Conduit
1/2	AS-3-50	0.67/ 17.0	0.94/ 23.9	10-4, 8-2, 8-3, 1-1, Armored Cable; 1/29 Flexible Conduit
3/4	AS-4-50	0.79/ 20.1	1.16/ 29.5	8-4, 6-2, 6-3, Armored Cable; 3/49 Flexible Conduit

Trade Size Quantities (Inches)	Catalog Number	Dimensions in Inches/ Millimeters			Standard	
		A	B	C	Carton	Package
<b>NMC 2-Cond. 12 and 14</b>						
1 x 1/2	SN-400	0.73/ 18.5	0.13/ 3.3	1.12/ 28.4	100	10,000
1 x 1/2	SN-405	0.73/ 18.5	0.13/ 3.3	1.12/ 28.4	500	10,000
1 x 1/2	SN-410	0.73/ 18.5	0.13/ 3.3	1.12/ 28.4	—	15,000
<b>NMC 3-Cond. 10-12 and 14 Wire</b>						
1-1/4 x 9/16	SN-1000	0.80/ 20.3	0.14/ 3.6	1.37/ 34.8	100	5,000
1-1/4 x 9/16	SN-1050	0.80/ 20.3	0.14/ 3.6	1.37/ 34.8	500	5,000
1-1/4 x 9/16	SN-1100	0.80/ 20.3	0.14/ 3.6	1.37/ 34.8	—	10,000
<b>SE/U 3-Cond. No. 6</b>						
1-3/8 x 13/16	SN-3000	1.30/ 33.0	0.26/ 6.6	1.32/ 33.5	100	5,000