

# NEER Aluminum Service Entrance Pulling Ells

With Cover and Gasket

COMMERCIAL PRODUCTS: SERVICE ENTRANCE FITTINGS

Commercial Products

## SLB: Pulling Ells

### Applications

- To provide access to the inside of a service raceway.
- For wire pulling where the raceway changes direction.

### Features

- Cover and gasket included.

### Standard Material/Finish

- Diecast aluminum/epoxy powder coat
- Gasket: fiber

### Certifications and Compliances


- UL Standard: 514B
- UL Listed: E53330
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1

#### Note:


- SLBs are limited to No. 6 AWG maximum wire size. The maximum quantity of conductors is based on the maximum conductor fill for the trade size of the raceway (conduit).



SLB-50



SLB-125-XL



Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters		
		A	B	C
1/2	<b>SLB-50</b>	3.24/82.3	1.22/31.0	1.42/36.1
3/4	<b>SLB-75</b>	3.57/90.7	1.40/35.6	2.68/68.1
1	<b>SLB-100</b>	4.25/108.0	1.77/45.0	1.96/49.8
1-1/4	<b>SLB-125</b>	5.62/142.7	2.26/57.4	2.43/61.7
1-1/2	<b>SLB-150</b>	6.25/158.8	2.47/62.7	2.35/59.7
2	<b>SLB-200</b>	6.75/171.5	2.92/74.2	2.90/73.7

## SLB-XL: Extra Long Pulling Ells

### Applications

- To provide access to the inside of a service raceway.
- For wire pulling where the raceway changes direction.

### Features

- Cover and gasket included.

### Standard Material/Finish

- Diecast aluminum/epoxy powder coat
- Gasket: fiber

### Certifications and Compliances

- UL Standard: 514B
- UL Listed: E53330
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1

Trade Size (Inches)	Catalog Number	Dimensions in Inches/Millimeters		
		A	B	C
1-1/4	<b>SLB-125-XL</b>	7.87/199.9	2.56/65.0	2.35/59.7
2	<b>SLB-200-XL</b>	10.25/260.4	3.22/81.8	3.32/84.3