







# Fixture Hanger Accessories

Baymaster, Lumenmaster, Super-Baymaster

LIGHTING: GENERAL LIGHTING – AREA – LOW BAY

Lighting

		Catalog Number			
		Voltage	Fits Hubbell Plug No.	Pendant	Feed-Thru
<b>GHPHP Pendant with one 3/4"/19.1 mm hub, GHPHT with two 3/4"/19.1 mm hubs</b>					
<i>Furnished with assembled FS box, EFHM safety lock, receptacle and steel cover. Supports 200 lbs/90.7 kgs.</i>					
 <p>GHPHP</p>	 <p>GHPHT</p>	120	L5-15P	<b>GHPHP12</b>	<b>GHPHT12</b>
		208, 240	L6-15P	<b>GHPHP24</b>	<b>GHPHT24</b>
		277	L7-15P	<b>GHPHP27</b>	<b>GHPHT27</b>
		480	L8-20P	<b>GHPHP48</b>	<b>GHPHT48</b>
		Voltage	Fits Hubbell Receptacle No.	Cord Length Ft/M	Catalog Number
<b>Matching Cord Sets for above Receptacle Hangers</b>					
	120	L5-15R	2/6	<b>G-HCPL-2-12</b>	
			3/9	<b>G-HCPL-3-12</b>	
			4/1.2	<b>G-HCPL-4-12</b>	
	208, 240	L6-15R	2/6	<b>G-HCPL-2-24</b>	
			3/9	<b>G-HCPL-3-24</b>	
			4/1.2	<b>G-HCPL-4-24</b>	
	277	L7-15R	2/6	<b>G-HCPL-2-27</b>	
			3/9	<b>G-HCPL-3-27</b>	
			4/1.2	<b>G-HCPL-4-27</b>	
	480	L8-20R	2/6	<b>G-HCPL-2-48</b>	
			3/9	<b>G-HCPL-3-48</b>	
			4/1.2	<b>G-HCPL-4-48</b>	
		Size (Inches)	Length (A) Inch/Millimeters	Support Wt. Lbs/Kgs	Catalog Number
<b>FH—Hanger Loops With 5/8"/16.0 mm wire opening</b>					
 <p>FHLM      FHLF</p>	<b>FHLM—Male</b>		350/158.8	<b>FHLM-50</b>	
	1/2	3.88/98.6			
	3/4	4.13/104.9			
	<b>FHLF—Female</b>				
	1/2	3.25/82.6			
	3/4	3.25/82.6			
<b>FH—Hanger Hooks With 5/8"/16.0 mm wire opening, 3/8"/19.1 mm jaw opening</b>					
 <p>FHHM      FHFF</p>	<b>FHHM—Male</b>		200/90.7	<b>FHHM-50</b>	
	1/2	3.88/98.6			
	3/4	4.13/104.9			
	<b>FHFF—Female</b>				
	1/2	3.25/82.6			
	3/4	3.25/82.6			
<b>Fuse and Cartridge — Cartridges are furnished complete with two 10"/254 mm-long high temperature wire leads and 600 Volt fuse</b>					
	6 Amp	<b>G-F6</b>			
	10 Amp	<b>G-F10</b>			
	20 Amp	<b>G-F20</b>			
	30 Amp	<b>G-F30</b>			