





FB415




FB426




FB426F



FB415



FB426F



FB426

Press On Fan & Fixture Mounting Boxes



The fastest and easiest way to mount fans and fixtures. Ships ready to install!

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | DESCRIPTION / CU. IN. | UNIT PKG | STD PKG | DIM A | DIM B | DIM C |
|----------------|--------------------------|---|----------|---------|-------|-------|-------|
| FB415 | 72167 | For 1/2" or 5/8" drywall 10.3 cu. in. | 25 | 25 | 2.250 | .500 | 4.250 |
| FB4150* | 72182 | For 1/2" or 5/8" drywall 10.3 cu. in. | 100 | 100 | 2.250 | .500 | 4.250 |
| FB426 | 72179 | For 1/2" or 5/8" drywall 16.0 cu. in. | 25 | 25 | 2.625 | .500 | 4.250 |
| ● FB426F | 25217 | For 1/2" and 5/8" drywall 16.0 cu. in. | 25 | 25 | 6.250 | 4.250 | 2.625 |



PATENTED.
MADE IN USA.

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided. *Bulk packing for lower cost. Refer to chart on page R-25 for load ratings and number of single conductors.

FEATURES AND BENEFITS



- Fan/fixture installation screws are parked and ready for easy fan/fixture bracket installation!
- No loose parts to misplace, totally self contained!
- Gripping tangs press hold to the joist while you reach for your screwdriver
- FB426F's flanged design forms a protective barrier against air infiltration
- UL rated: 70 lb fan, 200 lb fixture; CSA rated: 50 lb fan/fixture
- Comes with NM connector installed and mud cover in place
- 2 hour fire rating

FAN/FIXTURE BOX INCLUDES

- Press on box with ready to tighten center screw, installed NM cable connector, mud cover, second KO, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).



INSTALLATION INSTRUCTIONS (FB415)



- 1) Press box onto joist. Gripping tangs hold the box in place temporarily.
- 2) Tighten center screw to secure to joist.
- 3) Push NM cable through connector.
- 4) Remove two long, "parked" screws for installation of bracket.
- 5) Use the screws to install fan/fixture bracket through the oval slots in the box, directly into the joist.

