

SNAP-TITE® Connectors

With spring steel clip. For NM • SE • MCI • MCIA • Flex • AC cable. For steel and aluminum jacketed cables. Zinc die-cast.



840ST



8400ST

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
840ST	80070	3/8	1/2	100	1000	.485	.879	.858	.225 - .612
8400ST	80074	3/8	1/2	100	1000	.485	.879	.858	.225 - .612

Refer to pages C-13 and C-14 for complete cable ranges.


SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 7.

For connectors that cost less and install faster see page C-8.

PATENTED.




See Page E-1 for ring removal instructions



840ST

8400ST



NM Cable Connector


For NM cable. Zinc die-cast.



CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
841	00841	3/8	1/2	100	1000	.422	.825	1.105	.225 - .612

Refer to pages C-13 and C-14 for complete cable ranges.

For connectors that cost less and install faster see page C-8.



SNAP-TITE® Connector

With spring steel clip. For NM cable. Zinc die-cast.



CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
841ST	80068	3/8	1/2	100	1000	.510	.912	.920	.225 - .612

Refer to pages C-13 and C-14 for complete cable ranges.

SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 7.

PATENTED.



See Page E-1 for ring removal instructions

