18,000 Lumen

2' LED High Bay

REPLACES UP TO 250W MH / 4L T5 FL / 6L T8 FL







ILH218LL / ILH218L

- 18,870 / 20,240 **LUMENS**
- ⁴ 145 WATTS
- \$\\dot{130} / 139 **LPW**
- ⊕ 80 CRI
- **¾** 4500K **CCT**
- 10-10V DIMMING
- REC MNT HT
 14 FT to 20 FT



ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	VOLTS	
ILH218LL	18,000 Lumen LED High Bay with Glare Free Lens	18,870	120-277	
ILH218L	18,000 Lumen LED High Bay - No Lens	20,240	120-277	

Specs shown are for 4500K CCT. Also available in 4000K and 5000K. See Cut Sheet for more information.

ACCESSORIES

CATALOG#	DESCRIPTION	
CH36	Chain Set	
CH36HFC	Chain Set w/Hammer-On Flange Clip	
CA36	Cable Set	
MS360	360° Motion Sensor (120, 277V)	

MS360-480 360° Motion Sensor (208, 240, 480V)



Hanging Hooks Included

AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
ILH218LL	50°C (122°F)
ILH218L	50°C (122°F)

OPTIONS

ADD SUFFIX#	DESCRIPTION	ADD SUFFIX#	DESCRIPTION
xC*	3' Cord (No Plug)	М	Motion Sensor (120, 277V)**
xT*	3′ 120V Cord & Plug	M2	Motion Sensor (208, 240, 480V)**
xE*	3' 208V Cord & Plug	Р	Pendant Mount
xF*	3′ 240V Cord & Plug	IC	Integrated Control**
xS*	3' 277V Cord & Plug	4	480V Driver
EB	Emergency Back-Up		

^{*}x = 3 for 3' Cord; 6 for 6' cord, 10 for 10' cord; and 20 for 20' cord lengths

ENERGY SAVINGS ___

LED				HID		
ſ				TOTAL		
		ANNUAL	SOURCE	WATTAGE	ANNUAL	ANNUAL
	WATTAGE	COST	WATTAGE	USED	COST	SAVINGS
	145	\$64	250 MH	290	\$157	\$93
	145	\$64	4L T5 FL	238	\$129	\$65
	145	\$64	6L T8 FL	186	\$106	\$42













^{**}End Panel Mounted