



UNIT HEATER | PH5HWAC SERIES

CHARCOAL GRAY



IDEAL SPACES | Factories; Garages; Schools; Shipping Docks; Warehouses

COLORS | Charcoal Gray

DIMENSIONS | 22" L x 16" H (14" w/o bracket) x 8" D

TEMP RANGE | 40°-90° F

CFM | 210

- Air flow can be directed vertically, horizontally or any position in between
- Mounts either on wall or ceiling for primary or spot heating (bracket included)
- Built-in bi-metal thermostat; multiple wattage heat selector switch for precise amount of heat
- Fan-only switch for air movement when no heat is required
- Specially designed venturi outlet to meet required additional air throw in vertical position
- Advanced pull-through air flow design draws air across heating element for even air distribution and cooler element operation
- Heavy gauge die-formed steel housing and completely enclosed fan motor
- Aluminum-finned, copper-clad steel sheath heating element extends life due to cooler sheath temperature and faster heat dissipation
- Manual reset thermal cut-off button located on front for easy access

MODELS & SPECIFICATIONS

CATALOG NO.	UPC	VOLTS	WATTS	BTU/HR.	AMPS	SHIP WT. (LBS)
PH5HWAC	6 85360 15071 0	240	5000/3333	17060/11372	21.0/14.0	28
		208	3750/2500	12795/8530	18.0/12.0	
PHCS1B	Cord & Plug Assembly (Optional)					

AIR DELIVERY DATA			FAN MOTOR DATA			MAXIMUM EFFECTIVE MOUNTING HEIGHT		HORIZONTAL AIR THROW	WIRE SIZE
CFM	FPM	ΔT(°F)	VOLTS	RPM	HP	HORIZ.	VERT.		
210	550	71	240/208	1600	1/100	8	15	24	AWG 10

