
# Thomas@Betts





## Aluminum Lug T&B Catalog Number:

ATL2-38

**UPC Number:** 78378661083

Status: Active

**Description:** 

Aluminum One-Hole Lug - Straight Standard Barrel - max 35KV, 2 Str. Wire, 3/8 Bolt Size, Tin Plated, Pink

| TTITO, O/O BOIL GIZO, TITT TOLO      |  |
|--------------------------------------|--|
| Features                             |  |
|                                      | Made of high-conductivity seamless aluminum tub-                                       |
|                                      | ing. Tin plated for corrosion resistance.  |
|                                      | Specifically chamfered barrel for ease of installation.                                |
|                                      | Color-coded for matching die identification. Prefilled with oxide inhibiting compound. |
|                                      | UL Listed when installed with Blackburn, Burndy, T&B or Andersons Tools.               |
| General                              |  |
| Material                             | Aluminum   |
| Finish                               | Tin Plated   |
| Wire Size                            | 2 Str.   |
| Number of Studs                      | 1  |
| Stud Size                            | 3/8  |
| Tongue Angle                         | Straight   |
| Barrel Length                        | Standard   |
| Barrel Shape                         | Standard   |
| Die Color                            | Pink   |
| Dimension Information                | Time   |
|                                      |  |
| A (inches)                           | 27/32  |
| B (inches)                           | 29/32  |
| C (inches)                           | 7/16   |
| L (inches)                           | 2 1/6  |
| T (inches)                           | 3/16   |
| W (inches)                           | 3/4  |
| Specifications                       |  |
| Voltage Rating                       | 35KV   |
| Tooling                              |  |
| Connector 9 Tealing Chart            | Available on Website   |
| Connector & Tooling Chart  Packaging | Available on vvebsite  |
| rackaging                            |  |
| T&B Inner Pack                       | 10   |
| Package in Units                     | 100  |
| T&B Sold in UOM                      | Each   |
| T&B Weight Per UOM                   | 3.6 lbs. per 100   |
| Application Support                  |  |
| T&B Sales Drawings                   | wsd-000516   |
| T&B Instruction Sheets               | ta01325-tb2  |
| Notes                                |  |
|                                      |  |
|                                      | For use with aluminum conductor (concentric, com-                                      |
|                                      | pressed or compact). Also listed for use with copper conductor.                        |



Thomas & Betts - USA

Memphis, TN 38125 www.tnb.com

8155 T&B Blvd.

### Certifications

RoHS Compliance

Yes

### Certifications





File Nbr:

#### For further technical assistance, please contact us...

**T&B Technical Support** MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com