

BIBD2/03, 2-Sided, 3-Cond. Clear Ins. MultiTap

By Burndy
Catalog # [BIBD2/03](#)



#14 - 2/0 AWG, 3 Ports, Double-sided Entry, Al/Cu Rated, Clear Plastisol allows visual confirmation conductor is properly inserted

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer	No
EU RoHS Indicator	Yes	
Certification - UL Recognized	No	
Industry Standard(s)	UL 486A-486B	
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)	
Certification - ETL	No	
Standards - Industry Standards Met	UL 486A-486B	
Standards - RoHS Compliance Status	CM	
Certification - CSA Approved	Yes	
UL Listed	Yes	
Certification - UL Listed Direct Burial	No	

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0
-----------------------------	--

Conductor - AL Str Size	<ul style="list-style-type: none"> • 2/0 Str • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG
Conductor - AL Str Size Range	8 AWG-2/0 AWG
Conductor Size	14-2/0 AWG
Conductor - Copper Str Size Range	14 AWG - 2/0 AWG
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Screws	3
Connector Type	Multi Tap
Number Of Ports	3

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall	56 mm
Dimension - Height fraction	1.375 in
Dimension - Height inch	1.38 in
Package Height	0.000 in
Dimension - Height mm	35.1 mm
Dimension - Width fraction	1-14/25 in
Dimension - Width inch	1.56 in
Dimension - Width mm	40 mm
Dimension - Length Overall	2.19 in
inch	

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™

Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBD, Multi-Port
UPC 12 Digit	781810223949
UPC 14 Digit GTIN	00781810223949
Material	Aluminum
Hex Key	3/16
Plating Type	Unplated
UPC	781810223949

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	7200

Operational

Temperature Rating	194
--------------------	-----

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)



A Hubbell brand