



BIBS2503, 3-Cond. Clear Ins. Multi-Tap

By Burndy
Catalog # [BIBS2503](#)

#10 AWG - 250 kcmil, 3 Ports, Single-sided Entry, Al/Cu Rated,
Clear Plastics allows visual confirmation conductor is properly
inserted



Features

- Clear Platisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear platisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No


Conductor

Conductor - AL Str Size Range	10 AWG - 250 kcmil
Conductor Size	10 AWG-250 KCMIL
Conductor - Copper Str Size Range	10 AWG - 250 kcmil
Conductor Type	<ul style="list-style-type: none">• AL C Str-Size• CU C Str-Size

Configuration

Physical Attribute - Number of Screws	3
Connector Type	Multi Tap
Number Of Ports	3

Current



Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	75 mm
Dimension - Height inch	2.13 in
Package Height	0.000 in
Dimension - Height mm	54 mm
Dimension - Width inch	2.07 in
Dimension - Width mm	53 mm
Dimension - Length Overall inch	2.97 in

General

Insulation Type	Platisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type Plated	Allen N
Type	BIBS, Multi-Port
UPC 12 Digit	781810223994
UPC 14 Digit GTIN	00781810223994
Material	Aluminum
Hex Key	5/16
Plating Type	Unplated
UPC	781810223994

Logistics

Minimum Pack Quantity	1
Carton Quantity	24
Pallet Quantity	2304

Operational

Temperature Rating	194
--------------------	-----

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)