



BIBS2504, 4-Cond. Clear Ins. Multi-Tap

By Burndy
Catalog # [BIBS2504](#)

#10 AWG - 250 kcmil, 4 Ports, Single-sided Entry, Al/Cu Rated,
Clear Plastics allows visual confirmation conductor is properly
inserted



Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Certification - ETL	UL 486A-486B
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL 486A-486B
Certification - CSA Approved	CM
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes
	No


Conductor

Conductor - AL Str Size Range	10 AWG - 250 kcmil
Conductor Size	10 AWG-250 KCMIL
Conductor - Copper Str Size Range	10 AWG - 250 kcmil
Conductor Type	<ul style="list-style-type: none">• AL C Str-Size• CU C Str-Size

Configuration

Physical Attribute - Number of Screws	4
Connector Type	Multi Tap
Number Of Ports	4

Current



Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	99 mm
Dimension - Height inch	2.13 in
Package Height	0.000 in
Dimension - Height mm	54 mm
Dimension - Width inch	2.07 in
Dimension - Width mm	53 mm
Dimension - Length Overall inch	3.91 in

General

Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type Plated	Allen
Type	N
UPC 12 Digit	BIBS, Multi-Port
UPC 14 Digit GTIN	781810224014
Material	00781810224014
Hex Key	Aluminum
Plating Type	5/16
UPC	Unplated
	781810224014

Logistics

Minimum Pack Quantity	1
Carton Quantity	24
Pallet Quantity	1536

Operational

Temperature Rating	194
--------------------	-----

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)