

BIBD3502, 2-Sided, 2-Cond. Clear Ins. MultiTap

By Burndy
Catalog # [BIBD3502](#)

#10 AWG - 350 kcmil, 2 Port, Double-sided Entry, Al/Cu Rated, Clear Plastisol allows visual confirmation conductor is properly inserted



Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer	No
EU RoHS Indicator		Yes
Certification - UL Recognized		No
Industry Standard(s)	UL 486A-486B	
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)	
Certification - ETL		No
Standards - Industry Standards Met	UL 486A-486B	
Standards - RoHS Compliance Status	CM	
Certification - CSA Approved		Yes
UL Listed		Yes
Certification - UL Listed Direct Burial		No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG
-----------------------------	---

Conductor - AL Str Size	<ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil
Conductor - AL Str Size Range	8 AWG-350 kcmil
Conductor Size	10 AWG-350 KCMIL
Conductor - Copper Str Size Range	10 AWG - 350 kcmil
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	56 mm
Dimension - Height fraction	2.5 in
Dimension - Height inch	2.50 in
Package Height	0.000 in

Dimension - Height mm 63.5 mm
Dimension - Width inch 3.00 in
Dimension - Width mm 76 mm
Dimension - Length Overall inch 2.22 in

Material Aluminum
Hex Key 5/16
Plating Type Unplated
UPC 781810224083

General

Material - Hardware Aluminum
Insulation Type Platisol
Trade Name UNITAP™
Insulation Y
Sub Brand UNITAP
Physical Attribute - Screw Type Allen
Plated N
Type BIBD, Multi-Port
UPC 12 Digit 781810224083
UPC 14 Digit GTIN 00781810224083

Logistics

Minimum Pack Quantity 1
Carton Quantity 24
Pallet Quantity 1728

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)



A Hubbell brand