



## BIBD42, 2-Sided, 2-Cond. Clear Ins. MultiTap

By Burndy  
Catalog # [BIBD42](#)

#14 - 4 AWG, 2 Port, Double-sided Entry, Al/Cu Rated, Clear  
Plastisol allows visual confirmation conductor is properly inserted



### Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

### Application

For Indoor Use Only, Copper Or Stranded Aluminum

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

### Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 14 AWG</li> <li>• 12 AWG</li> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 Str</li> </ul>
Conductor - AL Str Size	<ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 6 AWG</li> <li>• 4 AWG</li> </ul>
Conductor - AL Str Size Range	8 AWG-4 AWG
Conductor Size	14-4 AWG

Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>

### Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

### Current

Voltage - Maximum	600 V
-------------------	-------

### Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	27 mm
Dimension - Height fraction	1.25 in
Dimension - Height inch	1.25 in
Package Height	0.000 in
Dimension - Height mm	31.8 mm
Dimension - Screw Size inch	1/4
Dimension - Width fraction	1-1/2 in
Dimension - Width inch	1.50 in
Dimension - Width mm	38 mm
Dimension - Length Overall inch	1.08 in

### General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBD, Multi-Port
UPC 12 Digit	781810223819
UPC 14 Digit GTIN	00781810223819
Material	Aluminum
Hex Key	1/8
Plating Type	Unplated

UPC 781810223819

**Logistics**

Minimum Pack Quantity 1  
Carton Quantity 100  
Pallet Quantity 9600

**Operational**

Temperature Rating 194

**Product Assets**

[Catalog \[English\]](#)  
[Catalog \[English\]](#)



A Hubbell brand