



## BIBD6002, 2-Sided, 2-Cond. Clear Ins. MultiTap

By Burndy  
Catalog # [BIBD6002](#)

#4 AWG - 600 kcmil, 2 Port, Double-sided Entry, Al/Cu Rated, Clear Plastisol allows visual confirmation conductor is properly inserted



### Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

### Application

For Indoor Use Only, Copper Or Stranded Aluminum

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

### Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> <li>• 300 kcmil</li> <li>• 350 kcmil</li> <li>• 400 kcmil</li> <li>• 450 kcmil</li> <li>• 500 kcmil</li> </ul>
-----------------------------	--

Conductor - AL Str Size	<ul style="list-style-type: none"> <li>• 550 kcmil</li> <li>• 600 kcmil</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> <li>• 250 kcmil</li> <li>• 266 kcmil</li> <li>• 300 kcmil</li> <li>• 336 kcmil</li> <li>• 350 kcmil</li> <li>• 397 kcmil</li> <li>• 400 kcmil</li> <li>• 450 kcmil</li> <li>• 477 kcmil</li> <li>• 500 kcmil</li> <li>• 550 kcmil</li> <li>• 556 kcmil</li> <li>• 600 kcmil</li> </ul>
Conductor - AL Str Size Range	4 AWG - 600 kcmil
Conductor Size	4 AWG-600 KCMIL
Conductor - Copper Str Size Range	4 AWG - 600 kcmil
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>

### Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

### Current

Voltage - Maximum	600 V
-------------------	-------

### Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall	69 mm

Dimension - Height fraction	2.75 in
Dimension - Height inch	2.75 in
Package Height	0.000 in
Dimension - Height mm	69.9 mm
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm
Dimension - Length Overall inch	2.72 in

### General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBD, Multi-Port

UPC 12 Digit	781810224151
UPC 14 Digit GTIN	00781810224151
Material	Aluminum
Hex Key	3/8
Plating Type	Unplated
UPC	781810224151

### Logistics

Minimum Pack Quantity	1
Carton Quantity	45
Pallet Quantity	1575

### Operational

Temperature Rating	194
--------------------	-----

### Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)



A Hubbell brand