



BISR350, Clear Insulated Splice Reducer, #10 AWG - 350 kcmil

By Burndy
Catalog # [BISR350](#)

Aluminum UNITAP In-Line Splice Reducer, Clear Insulation, #10 AWG - 350 kcmil



Features

- Type BISR In-Line Splice/Reducers are easily installed on code conductor
- UL486B Listed, Dual rated AL9CU for any stranded copper or stranded aluminum applications

Application

For Indoor Use Only

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	<ul style="list-style-type: none"> • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil
Conductor - AL Str Size Range	10 AWG - 350 kcmil
Conductor - Copper Str Size	<ul style="list-style-type: none"> • #10 • 9 AWG • 8 AWG

- 7 AWG
 - 6 AWG
 - 5 AWG
 - 4 AWG
 - 3 AWG
 - 2 AWG
 - 1 AWG
 - 1/0
 - 2/0 AWG
 - 3/0 AWG
 - 4/0 AWG
 - 250 kcmil
 - 300 kcmil
 - 350
- | | |
|-----------------------------------|--|
| Conductor Size | 10 AWG-350 KCMIL |
| Conductor Type | <ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size |
| Conductor - Copper Str Size Range | 10 AWG - 350 kcmil |

Configuration

Physical Attribute - Number of Screws	2
Number Of Ports	2
Connector Type	In-Line

Current

Operating Voltage	600 V
Voltage - Maximum	600 V

Dimensions

Package Height	0.000 in
Dimension - Height mm	60 mm
Dimension - Height inch	2.35 in
Dimension - Height fraction	2.3333333333333335 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	118 mm
Dimension - Width fraction	1-17/50 in
Dimension - Width mm	34 mm
Dimension - Width inch	1.34 in
Dimension - Length Overall inch	4.63 in

General

Insulation Type	Plastisol
Trade Name	UNITAP™
Material - Hardware	Aluminum
Insulation	Y
Physical Attribute - Screw Type	Allen
Plated	N
Sub Brand	UNITAP
UPC	781810134092
Type	BISR, In-Line
Hex Key	5/16 in
Material	Aluminum
Plating Type	Unplated
UPC 12 Digit	781810134092

UPC 14 Digit GTIN

00781810134092

Logistics

Minimum Pack Quantity	1
Pallet Quantity	2160
Carton Quantity	60

Operational

Temperature Rating	90 °C
--------------------	-------

Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved
BRDY-BISR350-SPEC-EN | REV 5/2026