



BURNDY Catalog Number
UPC Number
Description
Status

ES2R4W
7818101414588
2 ACSR-6 AL/CU INS SE CO
Active

Web Use
BURNDY Product Line

Product Description

General

Insulated aluminum service entrance compression sleeve for combinations of insulated Copper, Aluminum and ACSR conductors

Conductor(s)

ACSR Size (Side A) - Range
Copper Solid Size (Side A) - Range
ACSR Size (Side B) - Range
Copper Str Size (Side B) - Range
Aluminum Size (Side A) - Range
Copper Str Size (Side A) - Range
Aluminum Size (Side B) - Range
CopperSolid Size (Side B) - Range

2 (6/1) Sparrow AWG-2 (7/1)
Sparate AWG
N/A
6 (6/1) Turkey AWG
6 AWG-5 AWG
2 AWG-1 AWG
2 AWG-1 AWG
6 AWG-5 AWG
N/A

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

N
N
Compliant
N
N

Physical

Color Code (Side A)
Color Code (Side B)
Insulation Type
Insulated (Yes or No)

Red
Blue
Nylon
Y

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175