



BURNDY Catalog Number K2A29U
UPC Number 7818106001088
Description TWO:6STR-250 DUAL
 RATED
Status Active

Web Use
 BURNDY Product Line

Dimensional

Width (in) 1.66
 Length (in) 2.56
 Bolt Hole Size (in) 0.38
 Thickness 0.25
 D - in 1.50
 Pad Width (in) 1.66
 N (in) 0.5

General

Number of Conductors 2
 Number of Holes 1
 Product Description Aluminum Universal
 Terminal, 2 Conductor, 1
 Hole, 6 AWG (Str)-250
 kcmil, 3/8" Stud, 2
 Screws, Al/Cu Rated, Tin
 Plated

Conductor(s)

Aluminum Size (Range) 6 AWG-250 kcmil
 Copper Solid Size (Range) N/A
 Copper Stranded (Range) 6 AWG-250 kcmil

Physical

Installation Torque 275
 Type of Plating Tin
 Connector Type Terminal
 Bolt Hole Size 3/8
 Plated (Yes or No) N
 Product Material Aluminum

Approvals / Certifications

Rated for Direct Burial N
 UL Listed Y
 CSA Certified Y
 ROHS Compatible Exempt
 UL Recognized N
 CULUS N
 Industry Standards UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA
 47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies
 47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175