



BURNDY Catalog Number	K3A29U4N
UPC Number	7818106011299
Description	THREE:6STR-250 NEMA
Status	Active

Web Use
BURNDY Product Line

	Dimensional
Width (in)	2.81
Length (in)	4.00
Bolt Hole Size (in)	0.57
Thickness	0.31
D - in	3.00
Pad Width (in)	3.02
E - in	1.75
N (in)	0.63

	General
Number of Conductors	3
Number of Holes	4
Product Description	Aluminum Universal Terminal, 3 Conductor, 4 Hole, 6 AWG (Str)-250 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 3 Screws, Al/Cu Rated, Tin Plated

	Conductor(s)
Aluminum Size (Range)	6 STR - 250 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	6 AWG-250 kcmil

	Physical
Installation Torque	275
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	9/16
Plated (Yes or No)	Y
Product Material	Aluminum

	Approvals / Certifications
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

BURNDY Technical Services

47 East Industrial Park Drive

47 East Industrial Park Drive