



BURNDY Catalog Number KA29U
UPC Number 7818103701555
Description 6STR-250 DUAL RATED
Status Active

Web Use
 BURNDY Product Line

Dimensional

Width (in) 1.00
 Length (in) 2.00
 Bolt Hole Size (in) 0.31
 Thickness 0.25
 D - in 0.94
 Pad Width (in) 1.02
 N (in) 0.47

General

Number of Conductors 1
 Number of Holes 1
 Product Description Aluminum Universal Terminal, 1 Hole, 6 AWG (Str)-250 kcmil, 5/16" Stud, 1 Screw, Al/Cu Rated, Tin Plated

Conductor(s)

Aluminum Size (Range) 6-250
 Copper Solid Size (Range) N/A
 Copper Stranded (Range) 6-250

Physical

Installation Torque 275
 Type of Plating Tin
 Connector Type Terminal
 Bolt Hole Size 5/16
 Plated (Yes or No) Y
 Product Material Aluminum

Approvals / Certifications

Rated for Direct Burial N
 UL Listed Y
 CSA Certified Y
 ROHS Compatible Exempt
 UL Recognized N
 CULUS N
 Industry Standards UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA
 47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies
 47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175