



BURNDY Catalog Number	KSA4/0
UPC Number	7818101535122
Description	TRITAP SERVIT 4/0-6STR
Status	Active

Web Use
BURNDY Product Line

	Dimensional
Width (in)	1.13
Height (in)	1.17
Size (Hex) or Size (Bolt)	1-3/16
Cross Flats	1.49
Size (Hex) or Size (Bolt) - in	1.19
B Length (in)	1.90
Bolt Diameter (in)	1.13
Min Tap Size with Max Run Size	#4/0 Str. (.528) - \$6 Str. (.184)
Max Tap size with Max Run Size	#4/0 Str. (.528) - #4/0 Str. (.528)
Min Tap Size with Min Run Size	#2 Str. Compact (.268) - \$6 Str. (.184)
B Length (Fraction)	1-8/9

	General
Product Description	Aluminum Split Bolt, (Run, Tap):: Al-Al: 4/0 AWG (Str), 4/0 AWG (Str), Al-Cu: 2 AWG (Str), 6 AWG (Str), Cu-Cu: 4/0 AWG (Str), 6 AWG (Str), Tin Plated

	Conductor(s)
Aluminum Run Size (Range)	2 AWG-4/0 AWG
Copper Tap Range	6 AWG-4/0 AWG
Copper Stranded Run (Range)	2 AWG-4/0 AWG
Copper Solid Tap (Range)	4 AWG-4/0 AWG
Aluminum Tap Size (Range)	6 AWG-4/0 AWG

	Physical
Installation Torque	500
Type of Plating	Tin
Plated (Yes or No)	Y
Product Material	Aluminum

	Approvals / Certifications
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us