



BURNDY Catalog Number QN14M25X03D
UPC Number 7818102935155
Description MALE DISC 16-14AWG-
NYLON
Status Active

Web Use
BURNDY Product Line

Dimensional

Tab Size .250 X .032
Strip Length 3/8"
Width (in) 0.25
Length (in) 0.98
F - Spacing (in) (Width -
Center to Center) 0.08
B Length (in) 0.17

General

Product Description Brass Male Quick
Disconnect, 16-14 AWG,
Nylon Insulated, Funnel
Entry, Tin Plated

Other

Bulk Package QN14M25X03B

Approvals / Certifications

UL Listed N
CSA Certified N
ROHS Compatible Compliant
UL Recognized N
CULUS N
Industry Standards UL467

Conductor(s)

Copper Solid Size (Range) N/A
Copper Stranded (Range) 16 AWG-14 AWG

Physical

Type of Plating Tin
Connector Type Male Disconnect
Insulation Type Nylon
Plated (Yes or No) Y

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Services
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175