



On Line Catalog



BURNDY Catalog Number
UPC Number
Description
Status

YA262TC38
 7818105023966
 CUHYLUG 2/0STR 2HOLE 3/8
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Straight
 3.78
 Standard
 Chamfered
 0.39
 Long
 0.12
 1.50
 0.83
 1.00
 1-9/16

General

Number of Holes

2
 CU Compression Terminal Code
 Conductor, Beveled Entry, 2
 Hole/W/oInspWindow,
 2/0AWG(Code) 125(Navy), 600V-
 35kV, 3/8" Stud, 1" Spacing, Lng
 bbl, Tin Plated

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 2/0 AWG
 N/A
 2/0 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 3/8
 Black
 Y
 13
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Y
 Y
 Compliant
 N
 N
 UL468A-468B

Documentation

For further technical assistance, please contact us